Form 3160-5 (Provember 1983) (Formerly 9-331)		UNITED STATES BUBMIT IN TRIPLICATES (Other Instructions on re- OF THE INTERIOR (Other Instructions on re- verse side) BUREAU OF LAND MANAGEMENT					Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. SF079162 6. IF INDIAN, ALLOTTES OR TRIBE NAME			
(Do n	SUND!	RY NO	ICES AND REI	PORTS OF	WELLS k to a different reservoir.	9. 13	IRUIAN, ALLOITE			
i.							7. UNIT AGRESMENT NAME			
2 NAME OF	, want	OT BAL		£ + 3 = 2	⋰⋏⋏⋵⋏⋏⋺⋰⋛⋐⋬⋛⋛	8. 7.	ARM OR LEASE MAI	48		
DEPCO,				87 AU	G-3 AM 9:50		MKL			
3. ADDRESS O						9. 17	BLL NO.			
		Blda -	110 16th Stree	et ARPHAY	PON REGUBREE AREA		2			
4. LOCATION OF WELL (Report location clearly and in accordance with any State (requirements X C () See also space 17 below.) At surface NW-SW 1592' FSL, 847' FWL							PIELD AND POOL, O	R WILDCAT		
							So. Blanco	P.C		
							11. SBC., T., R., M., OR BLK. AND SURVEY OR ARBA			
							502751 Va 2222	•		
							Sec. 5, T26N-R7W			
14. PERMIT NO.			15. ELEVATIONS (Sho	15. ELEVATIONS (Show whether DF, RT, CR, etc.)			12. COUNTY OR PARISE 18. STATE			
NA				6033' GR			Arriba	NM		
						O.I.	.			
16.		Check A	ppropriate Box To	Indicate Nat	ture of Notice, Report, o	or Other	Data			
	NOT	ICE OF INTE	NTION TO:	1	803	SEQUENT B	EPORT OF:			
			PULL OR ALTER CASING		WATER SHUT-OFF		REPAIRING	WELL X		
	TER SHUT-OFF			'	FRACTURE TREATMENT		ALTERING C	ASING		
FRACTURI			MULTIPLE COMPLETE		SHOOTING OR ACIDIZING		ABANDONME	*****		
BHOOT OI	R ACIDIZE		ABANDON*							
REPAIR WELL		CHANGE PLANS		(Other)		its of multiple completion on Well appletion Report and Log form.)				
(Other)					Completion or Reco details, and give pertinent da ns and measured and true ve	tes Inclu	ting estimated da	te of starting and		
7-08-87	MTRII									
	2001-11	Pulled tbg w/pkr. Set BP @ 2027'. Ran tbg w/pkr. Found holes in csg from 380'-1143'. Set tbg w/pkr @ 319'. Mixed 200 sx cmt. Displaced down tbg. Found TOC in csg @ 439'. Set tbg on pkr @ 319'. Mixed 50 sx cmt. Staged cmt								
7-10-87	helow n	below pkr. Cleaned out w/bit from 475'-550'. Set tbg on pkr @ 320'. Mixed 100 sx cmt.								
7-11-87	Staged	Staged cmt below pkr to 300 psi. SI. Ran tbg & bit. Drld cmt from 360' to 486'. Tstd 7" csg w/pkr to 1000 psi.								
7-13-87	uald fo	uold for 15 min. Rap the w/bit. Drld cmt from 486' to 6/0'.								
7-14-87	+0 800	Tested 7" csg to 800 psi. Held ok. Drld cmt from 670' to 852'. Tested 7" csg to 800 psi. Drld cmt from 852' to 1145'. Cleaned out to top of BP. Tstd 7" csg to 800 psi.								
7-1 5-87	Drld cm	t from	852 to 1145'.	Cleaned	is to 1000 pgf bo	13 ok	TTH to re	etrieve BP.		
7-16-87			кer @ 320'. 1	stu /" Cs	gg to 1000 psi, he	Lu ON•				
7-17-87	Retriev	Retrieved BP. Retrieved BP. Retrieved BP. Retrieved BP. Retrieved BP. Retrieved BP.								
7-18-87	-17-87 Retrieved Br18-87 Clnd out to 2158' w/sand pump. Ran tbg string. Set 70 jts 2-3/8" OD tbg @ 2 Swbd well dn to cleanup.									
7-29-87	Ran swb	. Swbd	off wtr. Flw	wd well to	o cleanup. Shut w			n market.		
					(O) E	G E I	AFW			
-					1113	JG - 71				
	(Mach (e spregoing	true and correct	minum Dis	st. Prod. SupOIL			yRECORD87		
SIGNED	19 /					DIST	.4			
	ee for Federal	or State o		TITLE		AUG 04 1987				
APPROVED BY							AKWINGTUN KES	UUKUE AREA		
	R.S		*See	Instructions	on Reverse Side	BY		Moses		