

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan  
Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 6-12-61  
Company PAN AMERICAN PETROLEUM CORP. Lease Jicarilla Apache 102 Well No. 2  
Unit X Sec. 3 Twp. 26N Rge. 4W Purchaser \_\_\_\_\_  
Casing 4-1/2 Wt. 11.6 I.D. 4.032 Set at 8111 Perf. 7988 To 8010  
Tubing 2-3/8 Wt. 4.7 I.D. 1.993 Set at 7936 Perf. - To -  
Gas Pay: From 7988 To 8010 L 7999 xG 70 est. -GL 3599 Bar.Press. 12  
Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well Single  
Single-Bradenhead-G. G. or G.O. Dual  
Date of Completion: 6-1-61 Packer None Reservoir Temp. \_\_\_\_\_

## OBSERVED DATA

Tested Through (Packer) (Choke) (Meter) Type Taps Flange

| Flow Data |                            |                              |                |                         |              | Tubing Data    |              | Casing Data    |              | Duration<br>of Flow<br>Hr. |
|-----------|----------------------------|------------------------------|----------------|-------------------------|--------------|----------------|--------------|----------------|--------------|----------------------------|
| No.       | (Packer)<br>(Line)<br>Size | (Choke)<br>(Orifice)<br>Size | Press.<br>psig | Diff.<br>h <sub>w</sub> | Temp.<br>°F. | Press.<br>psig | Temp.<br>°F. | Press.<br>psig | Temp.<br>°F. |                            |
| SI        | 7 days                     |                              |                |                         |              | 2130           |              | 2130           |              |                            |
| 1.        | 1 days                     | .750                         | 230            |                         |              | 313            |              | 706            |              | 1 hours                    |
| 2.        |                            |                              |                |                         |              |                |              |                |              |                            |
| 3.        |                            |                              |                |                         |              |                |              |                |              |                            |
| 4.        |                            |                              |                |                         |              |                |              |                |              |                            |
| 5.        |                            |                              |                |                         |              |                |              |                |              |                            |

## FLOW CALCULATIONS

| No. | Coefficient<br>(24-Hour) | $\sqrt{h_{wpf}}$ | Pressure<br>psia | Flow Temp.<br>Factor<br>F <sub>t</sub> | Gravity<br>Factor<br>F <sub>g</sub> | Compress.<br>Factor<br>F <sub>pv</sub> | Rate of Flow<br>Q-MCFPD<br>@ 15.025 psia |
|-----|--------------------------|------------------|------------------|----------------------------------------|-------------------------------------|----------------------------------------|------------------------------------------|
| 1.  | 12.3650                  |                  | 262              | 1.0000                                 | .9250                               | 1.031                                  | 3022                                     |
| 2.  |                          |                  |                  |                                        |                                     |                                        |                                          |
| 3.  |                          |                  |                  |                                        |                                     |                                        |                                          |
| 4.  |                          |                  |                  |                                        |                                     |                                        |                                          |
| 5.  |                          |                  |                  |                                        |                                     |                                        |                                          |

## PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)

Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 2362 P<sub>c</sub><sup>2</sup> 5,579,844

| No. | P <sub>w</sub><br>P <sub>t</sub> (psia) | P <sub>t</sub> <sup>2</sup> | F <sub>c</sub> Q | (F <sub>c</sub> Q) <sup>2</sup> | (F <sub>c</sub> Q) <sup>2</sup><br>(1-e <sup>-s</sup> ) | P <sub>w</sub> <sup>2</sup> | P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup> | Cal.<br>P <sub>w</sub> | P <sub>w</sub><br>P <sub>c</sub> |
|-----|-----------------------------------------|-----------------------------|------------------|---------------------------------|---------------------------------------------------------|-----------------------------|----------------------------------------------------------|------------------------|----------------------------------|
| 1.  |                                         |                             |                  |                                 |                                                         | 515,324                     | 5063320                                                  |                        | 1.1018                           |
| 2.  |                                         |                             |                  |                                 |                                                         |                             |                                                          |                        |                                  |
| 3.  |                                         |                             |                  |                                 |                                                         |                             |                                                          |                        |                                  |
| 4.  |                                         |                             |                  |                                 |                                                         |                             |                                                          |                        |                                  |
| 5.  |                                         |                             |                  |                                 |                                                         |                             |                                                          |                        |                                  |

Absolute Potential: 3325 MCFPD; n 0.75  
COMPANY PAN AMERICAN PETROLEUM CORPORATION  
ADDRESS Box 400, Farmington, New Mexico  
AGENT and TITLE F. W. Poell, Petroleum Engineer  
WITNESSED \_\_\_\_\_  
COMPANY \_\_\_\_\_

REMARKS

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

$Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.

$P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia

$P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

$P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

$P_f$  = Meter pressure, psia.

$h_w$  = Differential meter pressure, inches water.

$F_g$  = Gravity correction factor.

$F_t$  = Flowing temperature correction factor.

$F_{pv}$  = Supercompressability factor.

$n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .