## (SUBMIT IN TRIPLICATE)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Indian Agency
Hearille
Allottee Contract #115
Lease No.

OTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<b>X</b>
OTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	- 1
OTICE OF INTENTION TO TEST WATER SHUT-OFF		
OTICE OF INTENTION TO REDRILL OR REPAIR WELL.	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.	
OTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
OTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
OTICE OF INTENTION TO ABANDON WELL		·
(INDICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
	Village of the Control of the Contro	
		, 19.
ll No. "" 5-6 is located 1850 ft. fr	$\{rom \mid S \}$ line and $\{rom \mid W \}$ line of sec	c <b>6</b>
W/4 SW/4 6	Are negre	
(14 Sec. and Sec. No.) (Twp.)	(Range) (Meridian)	
Lanco Nongrando (Count	ty or Subdivision) (State or Territory)	
water ared		
e elevation of the derivat hour above sea l	level is <b>7120</b> ft.	
DET#	AILS OF WORK	
	···	obs, cem
te names of and expected depths to objective sands; show s ing points, and all	sizes, weights, and lengths of proposed casings; indicate mudding j l other important proposed work)	
te names of and expected depths to objective sands; show sing points, and all	sizes, weights, and lengths of proposed casings; indicate mudding july light indicate	
te names of and expected depths to objective sands; show sing points, and all de-3/4" hole to 6132" and set 3 %." J-35 1Af 8-R9 casing w/hehm	sizes, weights, and lengths of proposed casings; indicate mudding jil other important proposed work)  564, 28° of 55° 09 3-55 15, 5f and 1546, I float these at 6132,40°. Beach Rose	
te names of and expected depths to objective sands; show sing points, and all d-3/4" hole to 6132" and set 3 5/4" 3-35 146 8-29 casing w/hekes	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  \$84,28° of 55° 09 3-55 15,55° and 1546;  \$150at shee at 6152,40°, Beach Rose  1 w/150 as rag. 268 8:30 pm 4-30. Se	.91' line
to names of and expected depths to objective sands; shows ing points, and all d 6-3/4" hole to 6132" and set 3 5/4" J-35 1Af 8-29 casing w/School times of lines w/30 sx reg. Set load	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  \$84,28° of 55" CD 3-55 15,55 and 1546;  \$ float shoe at 6152,40°, Beach Rose  r w/150 as ray, PCS 8:30 pm 4-30, Sc  l coal and reversed 10 as. Total top	.91' line queen of li
to names of and expected depths to objective sands; shows ing points, and all d 6-3/4" hole to 6132" and set 3 52" J-55 1Af 6-29 casing w/School times of lines w/30 sx reg. Set load	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  1844, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55 15, 56° and 1546; 1864, 28° of 55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-55° 00 3-5	.91' line
to names of and expected depths to objective sands; shows ing points, and all d 6-3/4" hole to 6132" and set 3 5/4" J-35 1Af 8-29 casing w/School times of lines w/30 sx reg. Set load	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  \$84,28° of 55" CD 3-55 15,55 and 1546;  \$ float shoe at 6152,40°, Beach Rose  r w/150 as ray, PCS 8:30 pm 4-30, Sc  l coal and reversed 10 as. Total top	.91' line queen of li
to names of and expected depths to objective sands; shows ing points, and all d 6-3/4" hole to 6132" and set 3 5/4" J-35 1Af 8-29 casing w/School times of lines w/30 sx reg. Set load	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  \$84,28° of 55" CD 3-55 15,55 and 1546;  \$ float shoe at 6152,40°, Beach Rose  r w/150 as ray, PCS 8:30 pm 4-30, Sc  l coal and reversed 10 as. Total top	.91' line queen of li
to names of and expected depths to objective sands; shows ing points, and all d 6-3/4" hole to 6132" and set 3 5/4" J-35 14f 8-19 casing w/School times of lines w/30 sx reg. But load	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  \$84,28° of 55" CD 3-55 15,55 and 1546;  \$ float shoe at 6152,40°, Beach Rose  r w/150 as ray, PCS 8:30 pm 4-30, Sc  l coal and reversed 10 as. Total top	.91' line queen of li
to names of and expected depths to objective sands; shows ing points, and all d 6-3/4" hole to 6132" and set 3 5/4" J-35 1Af 8-29 casing w/School times of lines w/30 sx reg. Set load	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  \$44.28 of \$5" OD 3-55 15.35 and 1346; floor whose at 6132.40 . Reach Rose to 1350 at rog. PCS 6130 pt 4-30. So seed and reversed 10 st. Total top 1, rem logs and released rig 7100 pt 1	.91' line of 11: 6-2-5
to names of and expected depths to objective sands; shows ing points, and all d 6-3/4" hole to 6132" and set 3 5/4" J-35 1Af 8-29 casing w/School times of lines w/30 sx reg. Set load	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  \$44.28 of \$5" OD 3-55 15.35 and 1346; floor whose at 6132.40 . Reach Rose to 1350 at rog. PCS 6130 pt 4-30. So seed and reversed 10 st. Total top 1, rem logs and released rig 7100 pt 1	.91' line of 11: 6-2-5
to names of and expected depths to objective sands; shows ing points, and all d 6-3/4" hole to 6132" and set 3 5/4" J-35 14f 8-19 casing w/School times of lines w/30 sx reg. But load	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  584, 28° of 54° 00 3-55 15, 56 and 1546; float shoe at 6152,40°. Beach Roce is w/150 as rag. P05 5:30 pm 4-30. So seal and reversed 10 as. Tetd top of the logs and released ris 5:00 pm (REFF)  OIL CON. CO	.91' line of 11: 6-2-5
te names of and expected depths to objective sands; show sing points, and all ld 6-3/4" hele to 6132" and set 3 %" J-35 146 8-89 casing w/Behas near at 4013.16". Communical lines of lines w/50 az reg. Set load 15000. GR. Cleaned cut to 6148" CR.	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  564, 26 of 54 00 3-55 15.54 and 1546; float shoe at 6152,40 . Beach Rose is w/150 as rag. POS 8:30 pm 4-30. Si seed and reversed 10 as. Tetd top of the logs and released ris 9:00 pm (MAY 13 195) con. CON. CON. CON. CON. CON.	91' line poon of 14 6-2-5
to names of and expected depths to objective sands; shows ing points, and all id 6-3/4" hole to 6132" and set 3 52" 3-35 1Af 8-39 casing w/hehes eggs at 4613.16". Command lines of lines w/30 sm reg. Set look 1500f. Ch. Cleaned cut to 61A8" Ch.	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  364.28 of 54" CD 3-55 15.34 and 1346.  2 float thee at 6132.40 . Beach Rose to 130 at 13	91' line poon of 14 6-2-5
to names of and expected depths to objective sands; shows ing points, and all id 6-3/4" hole to 6132" and set 3 %" J-35 146 8-29 cacing w/Behon act 4613.16". Communical lines of lines w/30 ax reg. Set lead 15000. GR. Cleaned cut to 6148" GR.	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  364.28 of 54" CD 3-55 15.34 and 1346.  2 float thee at 6132.40 . Beach Rose to 130 at 13	91' line poon of 14 6-2-5
to names of and expected depths to objective sands; shows ing points, and all ld 6-3/4" hole to 6132" and set 3 52" 3-35 1Af 8-39 casing w/Behon east at 4013.16". Command lines of lines w/30 sx reg. Set look 1500%. Ck. Cleaned cut to 61A8" Ck.	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  184, 28 of 54 00 3-35 15, 34 and 1546; float those at 6152,40 . Beach Rose to 152,40 and 1546; float those at 6152,40 and 1546; float those at 6152,40 and 1546; float those to 152,40 and 1546; float those those to 152,40 and 1546; float those thos	91' line poon of 14 6-2-5
to names of and expected depths to objective sands; shows ing points, and all id 6-3/4" hole to 6132' and set 3 5/4" J-35 146 0-29 casing w/School ager at 4013.16'. Committee lines of lines w/30 az reg. Set lead 15600. GE. Cleaned cut to 6148' CE.	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  364.28 of 54" CD 3-55 15.34 and 1346.  2 float thee at 6132.40 . Beach Rose to 130 at 13	91' line poon of 14 6-2-5
to names of and expected depths to objective sands; shows ing points, and all id 6-3/4" hole to 6132' and set 3 5/4" J-35 146 0-29 casing w/School ager at 4013.16'. Committee lines of lines w/30 az reg. Set lead 15600. GE. Cleaned cut to 6148' CE.	sizes, weights, and lengths of proposed casings; indicate mudding july other important proposed work)  184, 28 of 54 00 3-35 15, 34 and 1546; float those at 6152,40 . Beach Rose to 152,40 and 1546; float those at 6152,40 and 1546; float those at 6152,40 and 1546; float those to 152,40 and 1546; float those those to 152,40 and 1546; float those thos	91' line poon of 14 6-2-5

An Anna and Anna and

100 NOO NO

The second secon

en de la companya de Antigen de la companya de la company