

NEW MEXICO OIL CONSERVATION COMMISSION  
GAS WELL TEST DATA SHEET - - SAN JUAN BASIN

(TO BE USED FOR FRUITLAND, PICTURED CLIFFS, MESAVERDE, & ALL DAKOTA  
EXCEPT BARKER DOME STORAGE AREA)

72-205

Pool Blanco Formation Mesa Verde County Rio Arriba  
Purchasing Pipeline El Paso Natural Gas Date Test Filed \_\_\_\_\_

Operator El Paso Natural Gas Lease Rincon Unit Well No. 101  
Unit L Sec. 1 Twp. 26 Rge. 7 Pay Zone: From 5022 To 5156  
Casing: OD 5-1/2 WT. 15.5 Set At 5275 Tubing: OD 2 WT. 4.7 T. Perf. 5169  
Produced Through: Casing \_\_\_\_\_ Tubing X Gas Gravity: Measured .714 Estimated \_\_\_\_\_  
Date of Flow Test: From 8/30/58 To 9/7/58 \* Date S.I.P. Measured 5/19/58  
Meter Run Size \_\_\_\_\_ Orifice Size \_\_\_\_\_ Type Chart \_\_\_\_\_ Type Taps \_\_\_\_\_

OBSERVED DATA

Flowing casing pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (a)  
Flowing tubing pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (b)  
Flowing meter pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (c)  
Flowing meter pressure (meter reading when Dwt. measurement taken):  
Normal chart reading \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (d)  
Square root chart reading (\_\_\_\_\_) <sup>2</sup> x spring constant \_\_\_\_\_ = \_\_\_\_\_ psia (d)  
Meter error (c) - (d) or (d) - (c) \_\_\_\_\_ ± \_\_\_\_\_ = \_\_\_\_\_ psi (e)  
Friction loss, Flowing column to meter:  
(b) - (c) Flow through tubing: (a) - (c) Flow through casing \_\_\_\_\_ = \_\_\_\_\_ psi (f)  
Seven day average static meter pressure (from meter chart):  
Normal chart average reading \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (g)  
Square root chart average reading (7.10) <sup>2</sup> x sp. const. 10 \_\_\_\_\_ = \_\_\_\_\_ psia (g)  
Corrected seven day avge. meter press. (p<sub>f</sub>) (g) + (e) \_\_\_\_\_ = \_\_\_\_\_ psia (h)  
P<sub>t</sub> = (h) + (f) \_\_\_\_\_ = \_\_\_\_\_ psia (i)  
Wellhead casing shut-in pressure (Dwt) 1086 psig + 12 = \_\_\_\_\_ psia (j)  
Wellhead tubing shut-in pressure (Dwt) 792 psig + 12 = \_\_\_\_\_ psia (k)  
P<sub>c</sub> = (j) or (k) whichever well flowed through \_\_\_\_\_ = \_\_\_\_\_ psia (l)  
Flowing Temp. (Meter Run) 72 °F + 460 \_\_\_\_\_ = \_\_\_\_\_ °Abs (m)  
P<sub>d</sub> = ½ P<sub>c</sub> = ½ (l) \_\_\_\_\_ = \_\_\_\_\_ psia (n)

Q = \_\_\_\_\_ X  $\left( \frac{\text{FLOW RATE CALCULATION}}{\frac{V(c)}{V(d)}} \right)^* = \underline{155} \text{ MCF/da}$   
(integrated)

DELIVERABILITY CALCULATION

D = Q 155  $\left[ \frac{P_c^2 - P_d^2}{P_c^2 - P_w^2} \right]^n = \frac{1.2355}{1.1720} = \underline{182} \text{ MCF/da.}$

SUMMARY

P<sub>c</sub> = 804 psia  
Q = 155 Mcf/day  
P<sub>w</sub> = 504 psia  
P<sub>d</sub> = 402 psia  
D = 182 Mcf/day

Company El Paso Natural Gas  
By Original Signed  
Title Harold L. Kendrick  
Witnessed by \_\_\_\_\_  
Company \_\_\_\_\_

\* This is date of completion test.  
\* Meter error correction factor

REMARKS OR FRICTION CALCULATIONS

GL	(1-e <sup>-S</sup> )	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-S</sup> ) R <sup>2</sup>	P <sub>t</sub> <sup>2</sup> (Column i)	P <sub>t</sub> <sup>2</sup> + R <sup>2</sup>	P <sub>w</sub>
<u>3691</u>	<u>.235</u>	<u>2.123</u>	<u>499</u>	<u>254,016</u>	<u>254,515</u>	<u>504</u>

Friction Negligible

D at 500 = 153

