



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **080312-B**
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input checked="" type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 23, 1960

INTEX-SOUTH PARR HILLO

Well No. **01-3** is located **1980** ft. from **N** line and **1980** ft. from **W** line of sec. **5**

SE of NW Section 5
(1/4 Sec. and Sec. No.)

26 N. 1 E.
(Twp.) (Range)

N.M.P.M.
(Meridian)

Puerto Chiquito
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the ~~surface~~ ^{ground} floor above sea level is **7102** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Run K-log to total depth 3434'.
2. Place cement plug 3400 to 3300'.
3. Pull 5 1/2" casing from 3026', place cement plug 1475' to 1375'.
4. Pull 8 5/8" casing from 1205' and place cement plug from 750' to 650'.
5. Place cement plug in 10 3/4" surface pipe with 4" cement.



I understand that this plan of work must receive approval in writing from the Geological Survey before operations may be commenced.

Company **INTEX OIL COMPANY**

Address **P.O. Box 1411**

Bakersfield, California

Phone **FA 4-4936**

By **R. B. Miller**
Title **Production Manager**