

4 2000
1 Confidential
1 Production
1 File

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Number 10-1-1000
Approved August 19-61
Indian Agency Mountain Apache

Allottee Contract 712

Lease RECEIVED

DEC 11 1961

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	U. S. GEOLOGICAL SURVEY
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	NOTION
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 7, 1962

Well No. W 3-6 is located 2460 ft. from SW line and 1510 ft. from W line of sec. 6

SW 1/4 Section 6
(1/4 Sec. and Sec. No.)

24N (Twp.) SW (Range)

(Meridian)

Southwestern P.C.
(Field)

Rio Arriba
(County or Subdivision)

RECEIVED
DEC 3 1961
OIL CON. DIST. 3

The elevation of the ground level near above sea level is 6672 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Shut rig from W 3-6. Rigged up. Drilled rat hole and mouse hole. Spud 6 a.m. 11-27-61. Drilling 9 7/8" hole at 41'. Drilled 9 7/8" hole to 176'. Run 4 joints 7 5/8" O.D. 26.400 2-75 8 1/2" O.D. casing. T.B. 197.21 set at 176' HSE connected with 75' mouse hole plus 25' O.D. - Seal against to surface. Run 2:30 p.m. 11-27-61. Rigged up. Pressure tested casing to 2000 psi for 30 minutes - held a.k. Initiating at 400'. T.B. 3425'. Wt. 6.9; Vis. 65. Run 111 joints 2 7/8" O.D. 6.50 2-43 8 1/2" O.D. casing. T.B. 3442.89 set at 3442' HSE. Cemented with 100 sacks of gal plus 75 sacks last 75' HSE. 2:30 p.m. Seal and pressure while cementing. Reperforated casing from 3442' casing. Maximum cementing pressure 2000 psi. Released rig 11:59 p.m. on 11-27-61.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Occidental Petroleum Corp.

Address 7000 Stockdale Highway
Richmond, California

By Original signed by T. A. Dugan
Title Committing Engineer

