

APPROVED

JUN 18 1956

Budget Bureau No. 42-R-359.2.
Approval expires 12-31-55.

Form G-231b

(April 1942) (Eng. Sgd.) J. W. LUNG

(SUBMIT IN TRIPLICATE)

Indian Agency

Jicarilla

Contract No. 151

UNITED STATES

Allottee

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Co. Lease No. 196184

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	X	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

JICARILLA APACHE TRIBE
OF INDIANS "K"

Farmington, New Mexico May 25, 1956

Well No. 1 is located 2178 ft. from [N] line and 1220 ft. from [E] line of sec. 3

SE/4 of NE/4 Section 3

T 26N

R 5W

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Blanco Mesa Verde

Rio Arriba

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is later ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The notice of intention to drill this well listed a proposal to drill with mud to a total depth and to drill Well No. 2 with gas from 3600' to 5800'. Because of conditions of terrain, Well No. 2 was drilled first and was drilled with mud. The present proposal is to drill this well (No. 1) with gas from 3600' to 5800'.

Present Proposed Program

CASING PROGRAM

Size	Weight	Depth
13-3/8"	18#	300'
8-5/8"	24#	3600'
5-1/2"	14# & 15.5#	5800'

CEMENTING PROGRAM

Circulate to surface
Circulate to 13-3/8" casing
Circulate to 8-5/8" casing

CORING PROGRAM

Pictured Cliffs

Low water loss mud with diesel additive from 300' to 3600'. Drill from 3600' to 5800'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.

Company Humble Oil & Refining Company

Address Box 1268

Farmington, New Mexico

RECEIVED
JUN 22 1956
OIL CON. DIST. DIV.
COPY
By Russell N. Lilly
Title District Superintendent

