

APPROVED

JUN 18 1956

(SUBMIT IN TRIPLICATE)

Indian Agency **Jicarilla**Contract No. **151**

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Co. Lease No. **196184**

Allottee

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDON	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED  
MAY 25 1956  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO**JICARILLA APACHE TRIBE  
OF INDIANS "K"****Farmington, New Mexico May 25, 1956**Well No. **1** is located **2178** ft. from **[N]** line and **1220** ft. from **[E]** line of sec. **3****SE/4 of NE/4 Section 3****T 26N****R 3W**

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

**Blanco Mesa Verde****Rio Arriba****New Mexico**

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is **later** ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The notice of intention to drill this well listed a proposal to drill with mud to a total depth and to drill well No. 2 with gas from 3600' to 5800'. Because of conditions of terrain, well No. 2 was drilled first and was drilled with mud. The present proposal is to drill this well (No. 1) with gas from 3600' to 5800'.

## Present Proposed Program

## CASING PROGRAM

Size	Weight	Depth
13-3/8"	120	300'
8-5/8"	24	3600'
5-1/2"	14 & 15.5	5800'

## CEMENTING PROGRAM

Circulate to surface  
Circulate to 13-3/8" casing  
Circulate to 8-5/8" casing

## CORING PROGRAM

Mudcore Cliffs

Low water loss mud with diesel additive from 300' to 3600'. Drill with gas from 3600' to 5800'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.

Company **Humble Oil & Refining Company**Address **Box 1268****Farmington, New Mexico**RECEIVED  
JUN 22 1956  
OIL CON  
M. KELLY  
SIGNED  
1417By **Russell**  
Title **District Superintendent**

RECEIVED

NOV 19 1959  
U.S. AIR FORCE  
HONOLULU, HAWAII

