



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____

Jicarilla Tribal

Allottee _____

Lease No. _____

FEB 21 1964

CON. COM.
DIST. 3

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 14, 1964

Well No. Hoyt 1-5 is located 1720 ft. from N line and 850 ft. from E line of sec. 5
NE 1/4 Sec. 5 26 North 4 West NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Gallup & Basin Dakota Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)
The elevation of the derrick floor above sea level is 7287 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spud 8:00 A.M. 1/2/64, Drilled 360' of 12 1/4" hole reamed to 17" .
 Ran 10 joints of 13 3/8" and set at 302' KB cemented with 270 sacks
 regular with 2% Ca Cl₂ Circulated to surface, plug down 11:00 A.M. 1/3/64.
 Drilled 12 1/4" hole to 4315' KB Ran 137 joints of 8 5/8" 32# casing
 set at 4314 KB cemented with 295 sacks 50-50 pos mix with 4% Gel, tailed
 in with 90 sacks regular with 2% Ca Cl₂ Plug down 4:40 P.M. 1/10/64.
 Gas Drilled to 8524 KB. Ran 133 joints of 5 1/2" 15.50# casing. Set from
 4220 to 8522 as a liner. Cemented with 385 sacks class "C" with 20%
 Diacel D and tailed in with 100 sacks class "A" with 4% gel. Bumped
 plug at 11:45 P.M. 1/18/64.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Consolidated Oil & Gas Inc.Address P.O. Box 2036Farmington, New MexicoBy Thomas M. Boyd, Jr.Title Area Superintendent
Thomas M. Boyd, Jr.