



U.S.G.S. + 6  
File + 1

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Indian Agency \_\_\_\_\_

Allottee \_\_\_\_\_

Lease No. \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 6, 1956

Well No. Y 2-1 is located 1070 ft. from N line and 1140 ft. from W line of sec. 9

24 Sec. and Sec. No. 24 24 24 24 24  
(Field) (County or Subdivision) (Range) (Meridian) (State or Territory)

The elevation of the ungraded ground above sea level is 670.0 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Propose to drill to 110', set 3-1/8" casing and cement to surface with 75' of regular cement. Then drill to 170', set 4" casing and cement with 100' of 80 gal cement and 75' of regular. Further set the 4" casing and further the fractured Middle formation with approximately 10,000 gallons of water. Run tubing and complete well. The 21/4 of Section 9, containing 139.21 acres, is dedicated to this well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company STANDARD OIL COMPANY

Address 300 Stone Building

Albany, New Mexico

By Ray Phillips, Jr.

Title Asst. Mgr. Prod. Operations