Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Mano	•	Fo	rmation_	MosaVer	de		_County		
nit	ial	Annu	al		Specia	al		_Date of '	re s t	-3-60
omp	any Gecide	ntal Petrol	eum Cor	P•L	ease	¥		Wel	1 No	1-6
	S									
lagi	ng 51 W	15.5 T	. D.	Set	at 7598	Pei	f. 5472		To_485	2
Pubi	ng 14" W	2.4 T	. D.	Set.	at 2543	Pei	2540	1	To 254	3
i ubi	Pay: From_	1852 To	5472	ī	xG	.650	-GL	1	Bar.Pre	55.
as.	ray: rrom_	0-10		مردس 			Time We	Dual-	Cas-Cas	
'rod	ucing Thru:		40	rub	7350	Sing	gle-Brade	nhead-G.	G. or G	.O. Dual
)ate	of Complet	ion:		Packer			neservo	Tr. lemb.		
					OBSERVE	D DATA		_		
lest	ed Through	(Prover) (Choke)	(Meter)				Type Tap		
 	(Prover)	Flow D		Diff.	Temp.	Tubing Press.		Casing D		Duration
No.	(Line)	(Orifice)					° _F .	psig	□ _F .	of Flow Hr.
SI	Size	Size	psig	h _w		1065		1065		
2. 3.		3/4"	243		400			728		
5.			 					<u> </u>	<u> </u>	
			,	F	LOW CALC	ULATION	S			
No.	Coefficient			ressure Flow Temp. Factor				ctor Factor Q-MCFPD		Q-MCFPD
No.	(24-Hou	ır) $\sqrt{h_v}$	$p_{\mathbf{f}}$	psia	Ft		Fg	Fpv		@ 15.025 psia
1.										3179
1. 2. 3.	12.3650			255	1.0198		.9608	1.029		3417
!:										
				PRE	ESSURE CA	LCUT ATI	ons			
as I	iquid Hydro	carbon Rat:	io		cf/bbl.		Speci	ific Gravi	ty Sepa	arator Gas
ravi	ty of Liqui	ld Hydrocarl	oons(1-e-s)		deg.		Speci P	fic Gravi	ty Flor	ring Fluid
c			(<u>/</u>				Ç -	,		
	P _{w}	-2 ·		(E 0)2	/ E	0)2	P _w 2	$P_c^2 - P_w^2$	C:	al. Pw
No.	Pt (psia)	$P_{\mathbf{t}}^2$	F _c Q	(F _c Q) ²	(1-	Q) ² e-s)	* w~	.c-, w		Pw Pc
$\frac{1}{2}$										
1. 2. 3. 4. 5.	949						964	276		4-29
5.										
	olute Potent PANY	tial: 91	46		MCFPD;	n	2.9			
A DDI	RESS NT and TITL	e T. A. Dud	ma. Cas	anitine .	Ingineer'	,				
WITI	VESSED									
COM	PANY				REMA	ARKS	<u> </u>			



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q T Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 600 F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}\mbox{\scriptsize I}$ Differential meter pressure, inches water.
- F_{g} Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

		المارين الماري	-
		ک	
		•	
	/		
i Language de la companya de la compa	,	-	٠
** * * * * * * * * * * * * * * * * * *		1000	6
	1 · .		
\$35.7			_
U. S. C	the state of the s	AND SHOWNERS BEING MARKET AN	سيد
Parameters of the Control of the Con		ے بریا <mark>کیونیدسیت</mark> است	٠.
Transmoner			
Kii:			,
The Control of the Co			_
	•	1	