## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised	12-1-55

Poc	ol <u>Tapacito</u>	Pictu	ured (	<u>liff</u> Fo	ormation	nPie	ctured C	liffs	County_	Rio Ar	riba	
Ini	tial X		_Annu	al		Spec	ial		Date of	Test	August 25, 1959	
Сол	pany South	ern Uni	ion Ga	s Comp	ant	Lease	Jicarill	a	We]	Ll No	3 <b>-</b> G	
Unit C Sec. 1 Twp. 26N Rge. 5W Purchaser Southern Union Gas Company												
Casing 51 Wt. 15.5 I.D. 4.950 Set at 4218 Perf. 4078 To 4173  Tubing 2-3/8 Wt. 4.7 I.D. 1.995 Set at 4075 Perf. 4055 To 4075												
	Gas Pay: From 4078 To 4173 L xG -GL Bar. Press.											
						•				_		
Dat	e of Complet	ion: A	ugust	2. 19	59 Packe	r	Sir	ngle-Brade Reservo	enhead-G.	G. or (	s.O. Dual	
	•							<del></del>				
CBSERVED DATA  Tested Through (Choke) (Mater)  Type Taps												
<del></del>		F)	low Da	ta				Data	Casing I	ata		
No.	, , ,	(Orifi	ice)		l			Temp.	Press.		of Flow	
SI	Size	Siz	ze	psig	h <sub>w</sub>	°F.		°F.		<sup>⊃</sup> F•	<del> </del>	
1.		3/	<u> </u>	347		61.	858		858 732		7 days 3 hours	
2 <b>.</b> 3.								-				
4. 5.												
5. 1	5. !											
<del></del>	FLOW CALCULATIONS  Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow											
No.				1		Fact	tor	Factor	Facto	r	Q-MCFPD	
	$(24-Hour)$ $\sqrt{h_{W}p_{f}}$			psia F <sub>t</sub>		F <sub>g</sub>		Fpv		@ 15.025 psia		
1. 2. 3. 4. 5.	12.3650				359	0.9990		0.9463	1.0	1	1.368	
3.												
5.												
					PRI	ESSURE CA	alcu ati	ONS				
Gas Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas												
Gravity of Liquid Hydrocarbons deg. Specific Gravity Flowing Fluid P <sub>C</sub> 870 P <sup>2</sup> 757												
Pw 714 Pw2 554												
No.	P <sub>w</sub> Pt (psia)	Pt <sup>2</sup>	Fc	2	$(F_cQ)^2$	(F <sub>0</sub>	Q) <sup>2</sup> -e <sup>-s</sup> )	P <sub>w</sub> 2	$P_c^2 - P_w^2$		Pw Pc	
1.								554	203			
$\frac{\tilde{3}}{3}$ .												
1. 2. 3. 4.			-							+		
Absolute Potential: 13,366 MCFPD; n 0.85  COMPANY SOUTHERN UNION GAS COMPANY  ADDRESS P. O. Box 815 Farmington, New Mexico												
AGENT and TITLE Thomas E. Fenno Engineer WITNESSED COMPANY												
REMARKS												

SEP1 5 1959
OIL CON. CCI

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q  $\equiv$  Actual rate of flow at end of flow period at W. H. working pressure (P<sub>W</sub>). MCF/da. @ 15.025 psia and 60° F.
- P<sub>c</sub>= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- $F_{DV}$  Supercompressability factor.
- n \_ Slope of back pressure curve.

Note: If  $P_{\mathbf{W}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{W}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .

In commence of the selection of the sele