



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Leola, Pa.  
Lease No. 31-1151  
Unit Breach "A"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	X	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	350
NOTICE OF INTENTION TO ABANDON WELL.....			

ILLEGIBLE

K NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 6, 1963

Well No. 7711 is located 27 ft. from N line and 900 ft. from E line of sec. 1

Section 1 26N 6W 104N  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Basin Leola Mio Arriba New Mexico  
(Field) (County or Subdivision) (State or Territory)  
Blanco Mesa Verde

The elevation of the derrick floor above sea level is 6622 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging logs, cementing points, and all other important proposed work)

TO 7711. Ran 5 1/2" casing as follows:  
0 to 6707, 15.5# J-55, Sals.  
6707 to 7711, 17.0# J-55, Sals.

Cemented thru shoe with 100 sks. 12% gel cement containing 12% gilsonite per sk. and 4/10% HA-4 followed by 100 sks. latex. Plug down at 9:35 PM, 8-4-63.

Cemented thru CV collar at 3606' with 175 sks. Inconor class C cement containing 4% gel and 1% Haled 9. Closed tool with 2500# pressure. Plug down 10:45 PM, 8-5-63. Top of this stage per temperature survey was 4260.

Ran 2" tubing on outside of 5 1/2" casing to 3306 and cemented with 175 sks. Inconor class C cement containing 4% gel and 1% Haled 9. Plug down 10:30 AM, 8-6-63.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cookins Oil Company

Address Box 780

Farmington, N. M.

By Frank Gray

Title Superintendent

