

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____	<input type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL _____		

RECEIVED
JUL 1 1957

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 27, 1957

Well No. Siouxville #2 is located 970 ft. from N line and 970 ft. from E line of sec. 1

Section 1
(4 Sec. and Sec. No.)

24-N 3-W
(Twp.) (Range)

N.M.P.M.
(Meridian)

Blanco
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 7175 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

After setting 2262' of 5 1/2" Liner on bottom at 6100' with 200 sz cement. Set retainer @ 3764', Cement over top @ 3438' with 100 sz cement, Maximum Pressure 3000 lbs. 400-12 Hrs. Drilled out and tested top of 5 1/2" Liner with 1000 lbs for 30 minutes. Tested OK. No break.

6100
2262



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company MACDONALD PETROLEUM COMPANY

Address P.O. BOX 433

MIDLAND, TEXAS

By

HARVE E. MYFIELD

Title Asst. Division Superintendent