Form	n 9-3 pril 19	331 b 52)	
			0
	2		
1			

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency	
Jicarilla	
Allottee	,
Lease No. Tribal l	

SUBSCOURT REPORT OF SHOOTING OR ACIDIZING. SUBSCOURT REPORT OF SHOOTING OR REPAIR. SUBSCOURT REPORT OF SHOOTING OR REPAIR. SUBSCOURT REPORT OF REPORT OF REPORT. SUBSCOURT REPORT OF SHOOTING OR REPAIR. SUBSCOURT REPORT OF REPAIR. SUBSCOURT REPORT OF SHOOTING OR REPAIR. SUBSCOURT REPORT OF REPORT. SUBSCOURT REPORT. SUBSCOURT REPORT OF REPORT. SUBSCOURT REPORT OF REPORT. SUBSCOURT REPORT. SUBSCOURT REPORT OF REPORT. SUBSCOURT REPORT. SUBSCOURT REPORT. SUBSCOURT REPORT. SUBSCOURT	NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
SUBSEQUENT REPORT OF REDRILLING OR REPAIR WELL SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF R		
SUBSCULENT REPORT OF REDRILING OR REPAIR WELL SUBSCULENT REPORT OF ADDADAD ORDICE OF INTENTION TO SHOOT OR ALIDEZ NOTICE OF INTENTION TO SHOOT OR ALIDEZ NOTICE OF INTENTION TO ALIDE OR ALIDE CASING ORDICE OF INTENTION TO ABANDON WELL ORDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) FILT OR ALIDE OR ALIDE CASING ORDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) January 4 Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) FILT OR ALIDE OR OTHER DATA Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) FILT OR ALIDE OR OTHER DATA Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) FILT OR ALIDE OR OTHER DATA Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) FILT OR OTHER DATA HURON FILT OR OTHER DATA January 4 January 4 J964 Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) FILT OR OTHER DATA January 4 J964 Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) FILT OR OTHER DATA January 4 J964 Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) January 4 January 4 J964 Huron (ell No. 3-2 is located 975 ft. from Notice or Other DATA) January 4 January 4 J964 Huron FILT OR OTHER DATA J964 J1964 J1964 J1964 J1964 Huron J1964 J196		
Supplementary well history. Supplementary well history. Supplementary well history.		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.
Annuary 4 19.64 Huron January 4 19.64	NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
January 4 19.64	NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY.
Huron Yell No. 3-2 is located 975 ft. from line and 810 ft. from line of sec. 2 NE 2 26N 4W NMPM (Meridian) Slanco Mesaverde Rio Arriba New Mexico (Plaku) (County of Subdivision) Fapacito Pictured Cliffs The elevation of the derrick floor above sea level is 7245 ft. KB 7233 GL DETAILS OF WORK Spudded 11/2/63. Drilled 17" hole to 306', ran 12-3/4" casing as surface, see at 306' KB and cemented with 250 sx. reg 2% Cacl2. Circulated cement to surfacile of 10-5/8" hole with mud to 4240'. Ran 8-5/8", 32 lb. casing, set at 422 Cemented with 260 sx. 50/50 pozmix, 2% gel. Bumped plug with 2000 psi at 3:30 A.M., 11/13/63. WOC 18 hrs., pressured on casing to 1250 psi with rig pound for 30 min., held okay. Gas drilled casing shoe on to 4264', wouldn't dust. Squee zed from 4112' to 4264' with 100 sx. reg., 4% Cacl2 to 1975 psi, held okay. WOC for 18 hrs. Drilled out with gas, no moisture, cement job ownsy. I understand that this plan of work must receive approval in writing by the Coological Survey before operations may be commenced. My 1964 Title President Hall 1975 Sherman Street Denver 3, Colorado Title President Hall 1975 Sherman Street Denver 3, Colorado Tanuary 4 President Hall 1964 Title President Hall 1964 Tanuary 4 NMPM New Mexico (State or Territory) (Stat	NOTICE OF INTENTION TO ABANDON WELL	
Huron Section	(Indicate above by Check Mar:	K NATURE OF REPORT, NOTICE, OR OTHER DATA)
Huron Section		Tanua my 4 10.64
Table 11/2/63. Drilled 17" hole to 306', ran 12-3/4" casing as surface, seat 306' KB and cemented with 250 sx. reg 2% CaCl ₂ . Circulated cement to sur Drilled 10-5/8" hole with mud to 4240'. Ran 8-5/8", 32 lb. casing, set at 422 Cemented with 260 sx. 50/50 pozmix, 2% gel. Bumped plug with 2000 psi at 3:30 A.M., 11/13/63. WOC 18 hrs., pressured on casing to 1250 psi with right own. Squeezed from 4112' to 4264' with 100 sx. reg., 4% CaCl ₂ to 1975 psi, held okay. WOC for 18 hrs. Drilled out with gas, no moisture, cement job okay. Inderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Denver 3, Colorado Title President Inn 17 1964 Inn 17 1964 President President President President President Inn 17 1964		January T
Gi Sea, said Sea, Na.) Capacito Pictured Cliffs he elevation of the derrick floor above sea level is .72.45 ft. KB Tapacito Pictured Cliffs he elevation of the derrick floor above sea level is .72.45 ft. KB DETAILS OF WORK Cate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coments ing points, and all other important proposed work) Spudded 11/2/63. Drilled 17" hole to 306', ran 12-3/4" casing as surface, see at 306' KB and cemented with 250 sx. reg 2% CaCl ₂ . Circulated cement to sur Drilled 10-5/8" hole with mud to 4240'. Ran 8-5/8", 32 lb. casing, set at 422 Cemented with 260 sx. 50/50 pozmix, 2% gel. Bumped plug with 2000 psi at 3:30 A.M., 11/13/63. WOC 18 hrs., pressured on casing to 1250 psi with right pount for 30 min., held okay. Gas drilled casing shoe on to 4264', wouldn't dust. Squeezed from 4112' to 4264' with 100 sx. reg., 4% CaCl ₂ to 1975 psi, held okay. WOC for 18 hrs. Drilled out with gas, no moisture, cement job okay. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Title President Title T	Huron ell No. 3-2 is located 975 ft. fr	$\{x\}$ line and 810 ft. from $\{x\}$ line of sec. 2
(Margo Mesaverde Rio Arriba New Mexico (Field) (County or Subdivision) Fapacito Pictured Cliff's he elevation of the derrick floor above sea level is 7245 ft. KB 7233 GL DETAILS OF WORK Late names of and expected depths to objective and state in a points, and all other important proposed versions of the derrick floor above sea level is 7245 ft. KB 7233 GL DETAILS OF WORK Late names of and expected depths to objective and state in a points, and all other important proposed versions of the derrick floor above sea level is 7245 ft. KB 7233 GL DETAILS OF WORK Late names of and expected depths to objective and state in proposed casings; indicate mudding Jobs, sements in a points, and all other important proposed versions of the depth of the points, and all other important proposed versions of the depth of the points, and all other important proposed versions of the death of the points, and all other important proposed versions of the points, and all other important proposed versions of the points, and all other important proposed versions of the points, and all other important proposed versions of the points, and all other important proposed versions of the points of the points, and all other important proposed versions of the proposed casings; indicate mudding Jobs, sements of the points of the points of the points of the proposed versions of		
Gradio (County or Subdivision) [County or Suddivision) [County or Sud		
Tapacito Pictured Cliffs he elevation of the derrick floor above sea level is 7235 GL DETAILS OF WORK Late names of and expected depths to objective sands, floor sizes, weights, and lengths of proposed easings, indicate mudding jobs, comentary proposed work) Equipment of the derrick floor above sea level is 7233 GL DETAILS OF WORK Late names of and expected depths to objective sands, floor sizes, weights, and lengths of proposed easings, indicate mudding jobs, comentary proposed work) Equipment of the derrick floor and all other important proposed easings, indicate mudding jobs, comentary proposed work) Equipment of the derrick floor and all other important proposed easings, indicate mudding jobs, comentary proposed work) Equipment of the derrick floor and sizes, weights, and lengths of proposed easings, indicate mudding jobs, comentary proposed work) Equipment of the derrick floor and sizes, weights, and lengths of proposed easings, indicate mudding jobs, coment in proposed work) Equipment of and expected depths to objective sands, floor sizes, sizes, and lengths of proposed easings, indicate mudding jobs, coments in proposed easings, indicate mudding jobs, coments in proposed work) Equipment of the derrick floor and lengths of proposed easings, indicate mudding jobs, coments in proposed easings, indicate mudding jobs, caster, and lengths of proposed easings, indicate mudding jobs, caster, and lengths of proposed easings, indicate mudding jobs, caster, and lengths of proposed easings, indicate mudding jobs, caster, say and in proposed easin	243-24 242-315-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3	
Extensive of and expected depths to objective and show sizes, weights, and longths of proposed casings, indicate mudding jobs, comentary points, and all other important proposed works? Equivariant to the street of the street	Capacito Pictured Cliffs ne elevation of the derrick floor above sea le	evel is <u>7245</u> ft. KB 7233 GL
Spudded 11/2/63. Drilled 17" hole to 306', ran 12-3/4" casing as surface, seat 306' KB and cemented with 250 sx. reg 2% CaCl ₂ . Circulated cement to surfacely company and that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. By Denver 3, Colorado Drilled 11/2/63. Drilled 17" hole to 306', ran 12-3/4" casing as surface, seat 306' KB and cemented with 250 sx. reg 2% CaCl ₂ . Circulated cement to surfacely casing by the CaCl ₂ by the 200 psi at 422 casing, set at 422 casing, set at 422 casing set at 422 casing, set at 422 casing solve on to 200 psi at 3:30 A.M., 11/13/63. WOC 18 hrs., pressured on casing to 1250 psi with right pound for 30 min., held okay. Gas drilled casing shoe on to 4264', wouldn't dust. Squeezed from 4112' to 4264' with 100 sx. reg., 4% CaCl ₂ to 1975 psi, held okay. WOC for 18 hrs. Drilled out with gas, no moisture, cement job okay. Junderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. May 1 1964 Denver 3, Colorado Title President		
huron Drilling Company, INC. ddress 715 Farmers Union Bldg. 1575 Sherman Street Denver 3, Colorado Title President 1964	•	
ddress 715 Farmers Union Bldg. 1575 Sherman Street Denver 3, Colorado Title President 1964	Spudded 11/2/63. Drilled 17" hold at 306' KB and cemented with 250 Drilled 10-5/8" hole with mud to 4 Semented with 260 sx. 50/50 pozm 3:30 A.M., 11/13/63. WOC 18 hoump for 30 min., held okay. Gallust. Squeezed from 4112' to 426 held okay. WOC for 18 hrs. Dril	e to 306', ran 12-3/4" casing as surface, so sx. reg 2% CaCl ₂ . Circulated cement to surface, Ran 8-5/8", 32 lb. casing, set at 42 mix, 2% gel. Bumped plug with 2000 psi at rs., pressured on casing to 1250 psi with ris drilled casing shoe on to 4264', wouldn't 4' with 100 sx. reg., 4% CaCl ₂ to 1975 psi,
Denver 3, Colorado Denver 3, Colorado Title President RIVED	Spudded 11/2/63. Drilled 17" hold at 306' KB and cemented with 250 Drilled 10-5/8" hole with mud to 40 Drilled 10-5/8" hole with mud to 40 Drilled 10-5/8" hole with mud to 40 Drilled 10-5/8 hole with 260 sx. 50/50 pozno 3:30 A.M., 11/13/63. WOC 18 hole with 260 min., held okay. Gallust. Squeezed from 4112' to 426 held okay. WOC for 18 hrs. Drillokay.	e to 306', ran 12-3/4" casing as surface, so sx. reg 2% CaCl ₂ . Circulated cement to su 4240'. Ran 8-5/8", 32 lb. casing, set at 42 nix, 2% gel. Bumped plug with 2000 psi at rs., pressured on casing to 1250 psi with ris drilled casing shoe on to 4264', wouldn't 4' with 100 sx. reg., 4% CaCl ₂ to 1975 psi, lled out with gas, no moisture, cement job
Denver 3, Colorado Title President RLULIV LD	Spudded 11/2/63. Drilled 17" hold at 306' KB and cemented with 250 Drilled 10-5/8" hole with mud to 4 Drilled 10-5/8" hole with 260 sx. 50/50 pozno 3:30 A.M., 11/13/63. WOC 18 hroump for 30 min., held okay. Gallust. Squeezed from 4112' to 426-10-10-10-10-10-10-10-10-10-10-10-10-10-	e to 306', ran 12-3/4" casing as surface, so sx. reg 2% CaCl ₂ . Circulated cement to su 4240'. Ran 8-5/8", 32 lb. casing, set at 42 nix, 2% gel. Bumped plug with 2000 psi at rs., pressured on casing to 1250 psi with ris drilled casing shoe on to 4264', wouldn't 4' with 100 sx. reg., 4% CaCl ₂ to 1975 psi, lled out with gas, no moisture, cement job
in 7 1964	Spudded 11/2/63. Drilled 17" hold at 306' KB and cemented with 250 Drilled 10-5/8" hole with mud to 4 Drilled 10-5/8" hole with must receive approval to 426 Drilled 10-5/8" hole work must receive approval to 426 Drilled 10-5/8" hole work must receive approval to 426 Drilled 10-5/8" hole work must receive approval to 426 Drilled 10-5/8" hole with mud to 4 Drilled 1	e to 306', ran 12-3/4" casing as surface, so sx. reg 2% CaCl ₂ . Circulated cement to su 4240'. Ran 8-5/8", 32 lb. casing, set at 42 nix, 2% gel. Bumped plug with 2000 psi at rs., pressured on casing to 1250 psi with ris drilled casing shoe on to 4264', wouldn't 4' with 100 sx. reg., 4% CaCl ₂ to 1975 psi, lled out with gas, no moisture, cement job
B. B. GOVERNMENT PRINTING OFFICE 16-84375-8	Spudded 11/2/63. Drilled 17" hold at 306' KB and cemented with 250 Drilled 10-5/8" hole with mud to 4 Drilled 10-5/8" hole with 260 sx. 50/50 pozm 8:30 A.M., 11/13/63. WOC 18 his bump for 30 min., held okay. Gallust. Squeezed from 4112' to 426 held okay. WOC for 18 hrs. Drilled okay. I understand that this plan of work must receive approval to 5 min.	e to 306', ran 12-3/4" casing as surface, so sx. reg 2% CaCl ₂ . Circulated cement to surface, Ran 8-5/8", 32 lb. casing, set at 42 mix, 2% gel. Bumped plug with 2000 psi at rs., pressured on casing to 1250 psi with ris drilled casing shoe on to 4264', wouldn't 4' with 100 sx. reg., 4% CaCl ₂ to 1975 psi, lled out with gas, no moisture, cement job
	Spudded 11/2/63. Drilled 17" hold at 306' KB and cemented with 250 Drilled 10-5/8" hole with mud to 40 Drilled 11/2 Dr	e to 306', ran 12-3/4" casing as surface, so sx. reg 2% CaCl ₂ . Circulated cement to surface, Ran 8-5/8", 32 lb. casing, set at 42 nix, 2% gel. Bumped plug with 2000 psi at rs., pressured on casing to 1250 psi with ris drilled casing shoe on to 4264', wouldn't 4' with 100 sx. reg., 4% CaCl ₂ to 1975 psi, lied out with gas, no moisture, cement job in writing by the Geological Survey before operations may be commenced. G COMPANY, INC. By President President