

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. S.F. 079162-C
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED
MAR 3 1952
OIL CON. COM.

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	DIST. <u>3</u>
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 1, 1952

Well No. 1-6 is located 990 ft. from N line and 990 ft. from W line of sec. 6

(NW/4)
(1/4 Sec. and Sec. No.)

26N. - 7W.
(Twp.) (Range)

N.M.P.M.
(Meridian)

Undesignated (Large Canyon area) Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6041 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Pictured Cliffs ss. location. Will set 200ft. of 10 3/4 inch surface casing. Approx. 2,130 ft. of 5 1/2 inch production string on top of Pictured Cliffs. Will cement surface string with sufficient cement to circulate to surface, and probably use 150 to 200 sac on production string.

Approx. total depth 2,200 ft.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Kingsley-Locke Oil Co.

Address Luhre Tower

Phoenix, Arizona

By F. C. Barnes

Title Geologist