STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

		I New Mexico	NORTHWEST N	EW MEXICO P	ACKER-LE/	AKAG:	E TEST	·		
erator		BIL PRODUCIN	G TX. & N.M.	INC. Lease	Jicari1	1a	Н	Wcl No.	2	
_		Sec. 02	26N	Rge	03W_		Coun	ty	Rio. Arriba	
well:	NAME OF RESERVOIR OR			TYPE OF P	ROD.	METHOD OF PROD. (Flow or Art. Lift)			PROD. MEDIUM (Tbg. or Csg.)	
Ipper npietion	Gavilan Fielderd Gills		Gas				TBC			
.ower npietion			Gas)W		TRG		
			PRE-FLO	OW SHUT-IN P	RESSURE D	ATA				
Hour, date shul-in Length of time shu			rt-in	SI press. psig	S		Stabilized? (Yes or No)			
Upper npietion	11-2	7-91	5 days	Length of time shut-in		489# SI press, palg		Stabilized? (Yes or No)		
Lower	Hour, date si									
mpletion	11-2	7-91	5 days		760#_					
		10 / 01		FLOW TEST		cing (Upo	er or Lowert L	OWER		
onimenced at (hour, date)* 12-4-91				PRESSURE		PROD. ZONE				
	ME , date)	LAPSED TIME SINCE*	Upper Completion	Lower Completion	TEMP.		REMARKS			
12-5-91		lst day	464#	760#	date		12-2-91		12-3-91	
12-6-91		2nd day	462#	760#	upper		489#		489#	
					lower	∳ ∍ [′] -	760#	1 - 12-3	76.0#	
							C. N. 18	14 242 4	M CPRE	
					ļ					
		uring test								
il:		ВОР							GOR	
ءد:	26		мс	PD; Tested thr	ı (Orifice or	Meter): <u>METER</u>			
			мір-т	EST SHUT-IN P		ATA		Slabilizad ¹	(Yes or No)	
Upper				ul-in	SI press, psig			Stabilized? (Yes or No)		
Lower			Length of time sh	Length of time shul-in		SI press. psig			Stabilized? (Yes or No)	
mpielloi ———	<u>"I</u>				') [SECTION	

DEC3 0 1991

REMARKS

FLOW TEST NO. 2

Lower Completio

PRESSURE

Upper Completion

Zone producing (Upper or Lower):

PROD. ZONE

TEMP.

								
	·. · · . · -	·		n pro-	المحمد ويوم الموادية الموادية الموادية الموادية ال			
	1			1				
								
					· · · · · · · · · · · · · · · · · · ·			
Production rate during test					-			
Oil:BOPD b	esed on	Bbls. in	Hours.	Grav	GOR			
G25:								
Remarks:				• .	- ·			
hereby certify that the information h	erein contained	is true and com	plete to the best	of my knowledge.	···			
Approved DEC 3 0 1991 New Mexico Oil Conservation Division	ion 1	9 O _F	Operator MOBIL EMP. & PROD. U.S. INC.					
Original Signed by CHARLE	C CHOLSON	Ву	By Leftoyd					
Ву		Tit	Title PRODUCTION TECH. I					
Title DEPUTY OIL & GAS INSPECTO	IR, DIST. #3	D2	te					

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) **

LAPSED TIME

SINCE **

TIME

(hour, date)

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Ten No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the aumosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced 200e shall remain shut-in while the 200e which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone teris: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azter District Office of the New Messoo Oil Conservation Division on Northwest New Messoo Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

