STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

tion Vell: Unit <u>C</u>	Sec5^	Twp26N	Rge	7 W	Co	untyR <u>io Arriba</u>	
	NAME OF RESERVOIR OR POOL			ROD.	METHOD OF PRI (Flow or Art. Life	· - · - · -	
por letion Gallup			T/A		T/A	T/A	T/A
rer letion Bas:					flow	tbg	
		PRE-FLO	OW SHUT-IN P	RESSURE DAT	Ά.		
Hour, date		Length of time shi	yt-In	81 press, palg 545		Stabilized? (Yes or No)	
etion 6/12/94 T/A How. dele shyl-in 5/12/94 Stoon 3 days			ut-in	Si press. psig 6 2 1		Stabilized? (Yes or No)	
.,,			FLOW TEST	NO. 1			
nenced at (hour, de	ste) #			Zone producing	(Upper or Lower):	lower	
TIME (hour, date)	LAPSED TIME	PRES Upper Completion	PRESSURE Upper Completion Lower Completion			REMARKS	
15/94	1 day	545	255				
16/94	2 days	545	250				
	·						
	, .						
duction rate		nn haad oo	Bhle	in Ho	ours.	_ Grav GOR	
	ВО					eter	
: 18		•	FPD; Tested thr		eter):		
			EST SHUT-IN	SI press. paig	I'A	Stabilized? (Yes or No)	
pper pletion			Length of time shul-in		<u> </u>	Stabilized? (Yes or No)	
Nour, date shut-in Length (Length of time si	nyt-16	Si press. peig			

JUL 1 8 1994 -

(Continue on reverse side)

OH CON. DIV. Tur. 8

FLOW TEST NO. 2

ommenced at (hour, de	ate) + +	,	Zone producing (Upper er Lower):		
TIME	LAPSED TIME	PRESSURE			(open a count)
(hour, date)	SINCE **	Upper Completion	Lewer Completion	PROD. ZONE TEMP.	REMARKS
·	·			ļ	
				 	
		<u>.</u>			
					
			1	I	
duction rate d	wing test				
	ВОРГ	D based on	Bhle in		n Grav GOR
		0.000	DOS. III	Hou	rs GOR
:		MCF	PD: Tested thru	(Orifice or Met	er):
			·		
reby certify th	iat the intormatio	n herein containe	ed is true and cor	nplete to the b	est of my knowledge.
proved	1 8 199	4	19 0	Derator LOU	is Dreyfus Natural Gas
lew Mexico Oi	I Conservation Di	ivision	/	perator <u></u>	Zeryrus Natural Gas
	// 1 1.	110	В	i	ene Seme
	Tarles J				3
			Ti	de Prod	duction Foreman
c DEPUT	Y OIL & GAS INSP	ECTUK, DIST. #	D	ate	2/94
					<u> </u>

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Terr No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours term: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day term: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Messeo Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).