

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(505) 334-6178 FAX: (505) 334-6170
http://lemnrd.state.nm.us/ocd/District II/Jodistric.htm

OIL CONSERVATION DIVISION

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	Louis Drey	Eus Nat. Ga	s_Lease Nar	me <u>Mil</u>	es Federal	Well No1	
_ocation of	Well:Unit Lette	<u>c Sec 5</u>	Twp26	<u>N_Rge_7</u>	W_API # 30-0_3	9-06759	
	NAME OF RES	1	F PROD.	METHOD OF PRO			
Upper Completion	Gallup	t/a		t./a	t./a		
Lower Completion	Basin I	gas		flow	tbg.		
		PRF_F	LOW SHUT-I	N DDESSII	DE DATA		
Upper	Hour, date shut-in	Length of time		SI press. Psig	Smellized? (Yes or No)		
Completion	9/5/99	3 days		0	yes		
Lower	Hour, date shut-in	Length of time	shut-in	SI press. Psig	Stabilized? (Yes or No)		
Completion	9/5/99	9/5/99			380	yes	
			FLOW TE	ST NO. 1			
Commenced at	(hour, date)*			Zone producin	g (Upper or Lower):		
TIME (hour,date)	LAPSED TIME	PRESSI	JRE	PROD. ZON	IE I	REMARKS	
	SINCE*	Upper Completion	ower Completion	TEMP.		C 1 10 3	
1/8/99	1 day	0	152		4 193		
1/9/99	2 days0		162		JAN 2000		
, -,	7			and the same of th		DEIVED E	
					UN S		
					3 3		
					126		
	1	<u> </u>				. 1700 CO VI	
oduction ra	te during test						
l:		BOPD based o	on	Bbls. in	Hours	_GravGOR	
as: 47		MCEDI); Tested thru	(Orifice or N	latas):		
<u></u>			o, rested and	(Office of N	leter): <u>met.er</u>		
 		MID-T	EST SHUT-IN	PRESSUR	E DATA		
Upper Completion	Hour, date shut-in		Length of time s	hut-in	SI press psig	Stabilized? (Yes or Nc)	
Lower Completion	Hour, date shut-in	Length of time shut-in		SI press. psig	Stabilized? (Yes or No)		

(Continue on reverse side)

FARED CTP

FLOW TEST NO. 2

Commence	d at (hour, date)*	*		Zone producing (Upper or Lowr):			
TIME	LAPSED TIME Since**	PRESSURE		PROD. ZONE	REMARKS		
(hour,date)		Upper Completion	Lower Completion	, NOO. ZONE	REMAR	(KS	
						_ 	
Dan dan aki a sa							
Production ra Oil: Gas:		based onMCFP	Bbis. D:Tested thru (C	inHour	sGrav	GOR	-
Remarks:							
hereby certif	the inform	nation herein con	tained is true and	d complete to the	bes of my knowledge.		
Approved19 Mexico Oil Conservation Division		_ Operator_	COULD DRE	14SUARY MAP	CAS	New	
			By <u>\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \</u>	le Lo	reference.		
			Title				
Title				ilis lav	\		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion
 are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain
 shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 5. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).