

DOWELL

JOB NO.

CEMENTING SERVICE REPORT

8-1-329

DISTRICT FARMINGTON 8 STATION FARMINGTON, N.M. DATE 9-18-62

OWNER Consolidated Oil & Gas CONTRACTOR Huron WELL NAME C.T. NO. 8

POOL TAPACIT LOCATION SEC 5 26N 3W COUNTY BLA AIRRA STATE

TYPE OF JOB INTERMEDIATE

USED FOLLOWING MEASURING LINE - DISPLACEMENT 118.3 TOP PLUG ✓ BOTTOM PLUG -

CEMENTING HEAD ✓ FLOAT EQUIPMENT BAVEY DISC - RETAINER -

WELL DATA

ROTARY - WT. DRILLING MUD - VISCOSITY - CABLE TOOL -

SIZE HOLE 8 1/2 TOTAL DEPTH 4022 BRADENHEAD -

CASING SIZE 7 7/8 WT. 2640 DEPTH 4022 CONDITION NEW THREAD PR.

SURFACE OR CONDUCTOR CASING SIZE - WT. - DEPTH - CONDITION -

LINER SIZE - WT. - TOP - BOTTOM - CONDITION - TYPE -

TUBING OR DRILL PIPE SIZE - WT. - DEPTH - CONDITION -

RETAINER TYPE - DEPTH - TAILPIPE - DEPTH -

PREVIOUS CEMENT JOB: DATE - KIND - SERVICE CO. - JOB NO. -

DETAILED RECORD OF SERVICE

TIME	PRESSURE	DETAIL
1200	9-18-62	ARRIVED ON LOCATION
1300		RIG-UP
1430		CIRC/RIG PUMP
1840		PUMP 1500L WATER & START MIXING CEMENT
1905		FINISH MIXING CEMENT & START DISPLACING
1930		PLUG DOWN - DID NOT BUMP
2030		BACK UP & WASH UP
2045	9-18-62	LEFT LOCATION

DEPTH STOP PLUG 3991 LEAVING 31 CEMENT IN PIPE -

WAS CIRCULATION EVER LOST NO WAS CEMENT CIRCULATED TO SURFACE NO

REMARKS OVER DISPLACED W/ 300L WATER PLUG did NOT BUMP

MATERIALS USED

FURNISHED BY CUSTOMER SACKS CEMENT - KIND CEMENT - WT. SLURRY -

PERCENT BENTONITE - PERCENT CACL - SACKS MUD -

OTHER MATERIALS -

FURNISHED BY DOWELL SACKS CEMENT 172.5 KIND CEMENT IDEAL CLASS A WT. SLURRY -

PERCENT BENTONITE 4% IN 50:50 PERCENT CACL - SACKS MUD -

OTHER MATERIALS 162 GALLONS DIACEL-10 97.5 SACKS IDEALITE

PERSONNEL AND EQUIPMENT USED

EMPLOYEE CEMENTER GAHINES TRUCK-CAR 1456-W5 Jack Gahines CEMENTING ENGINEER

EQUIPMENT OPERATOR STEWART 6574

EQUIPMENT OPERATOR HUFFMAN 6590

ROUND TRIP MILES: STATION TO WELL 220 C.D. ARRINGTON DISTRICT MANAGER OR STATION MANAGER

COPIES TO ☐ GENERAL OFFICE ☐ DISTRICT ☐ STATION ☐ CUSTOMER