

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Tract 251 Contract 000154

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Apache

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Jicarilla-Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 27 T 26N R 5W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.) All measure-
ments from KB
6525 GR 6538 KB12. COUNTY OR PARISH
Rio Arriba13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

Production Casing

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Production Casing

XX

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to a total depth of 7500'.

November 30, 1966 Ran 237 joints of 4 1/2" OD 11.6# 8rd J55 LT&C-S&C casing. Overall length 7520.52, effective length 7473.69. Cemented casing by Byron-Jackson. First stage cement 85 units of filler cement and 129 units of quality cement (1 unit filler cement, 1 sack class C, 1 sack Diamix A, 1/2% D30, 5 lbs. salt, 13.3 ppg slurry, 2.49 cu. ft. slurry yield; 1 unit filler cement, 1 sack class C, 2 sacks Diamix A, 10% Gel, 11 ppg, 6 cu. ft. slurry yield). Wait for 2 hours after plug down, circulating. Second stage cement, 246 units quality cement with 2% Gel and 16% Gilonite; 85 units of filler cement, circulated for 2 hours after plug down. Third stage cement, 350 units of filler cement, plug down. WOC.

	Overall length	Effective length
26 joints of 4 1/2" OD 11.6# 8rd J55 LT&C	805.76	799.07
211 joints of 4 1/2" OD 11.6# 8rd J55 S&C	6714.76	6674.67
Bakerstage Cementing collar Type J	2.02	1.80
Bakerstage Cementing collar Type JS	2.02	1.80
Baker Model C Circ. fillup collar	1.87	1.65
Baker Model C Circ. fillup shoe	2.06	2.06
	7528.19	7481.00

December 1, 1966 Tagged cement at 3460.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Superintendent

DATE November 9, 1966

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
F. SPRINGFIELD, N. M.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.