

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

87 080423

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

BENSON-MONTIN-GREER DRILLING CORP.

3. ADDRESS OF OPERATOR

221 Petroleum Center Building, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

175' FSL, 2090' FKL, Sec. 33, T-26N, R-1W

7. UNIT AGREEMENT NAME

Canada Ojitos Unit

8. FARM OR LEASE NAME

9. WELL NO.

10 (0-33)

10. FIELD AND POOL, OR WILDCAT

West Puerto Chiquito

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T-26N, R-1W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7533' GR

12. COUNTY OR PARISH 13. STATE

Rio Arriba New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5- 4-71 Perforated 7168-72' with 1 shot per foot, 7156-60' with 1 shot per foot, 7138-42' with 1 shot per foot, 7120-30' with 2 shots per foot, 7079-83' with 1 shot per foot. Plugged back with sand to 7250'.

5- 5-71 Spotted 500 gallons Dowell mud acid. Displaced acid into formation.

5-10-71 Sand-oil fractured using 150,000# 20/40 sand and 4,090 barrels crude oil. Average overall injection rate 87 BPM. Well sanded off during treatment. No apparent breakdown pressure. Maximum treating pressure 3500# (at sand-off), minimum 2400#, average 2600#. Inst. SDP 2000#.

5-24-71 Started pumping back load oil.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Vice-President

DATE

6-4-71

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:



DATE

JUN 9 1971

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to seal, plug, or abandon wells and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement plugs; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of setting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking for approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1983-O-685229

947 - 485