STATE OF NEW MEXICO

and beli

(This space Tox

Approved By

## OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 8750;

## APPLICATION FOR HULTIPLE COMPLETION

			OIL COM \$ 1982
Operator	County	Date	DIST 3
Caulkins Oil Company	Rio Arriba	9/28/82	3
Address	Lease	Well No.	
P.O. Box 780 Farmington	n, New Mexico Breec	h C 689 M	-
- P U-11	ction Township 12 26 Nort		
All Applicants for multip	le completion must com	plete Items 1 and 2 bel	OW.
<ol> <li>The following facts are submitted:</li> </ol>	Upper Zone	Intermediate Zone	Lower Zone
<ol> <li>Name of Pool and Formation</li> </ol>	Mesa Verde		Dakota
b. Top and Bottom of			
Pay Section (Perforations)	5488 5200	;	7524 7293
c. Type of production (Oil or Gas)	Gas		Gas
d. Hethod of Production (Flowing or Artificial Lift)	Flowing		Flowing
e. Daily Production Actual X Estimated	100 MCFPD	•	100 MCFPD
EKKXEGIXX Gas MCF <del>XXXX</del> XXXXXX			:
2. The following must be a	attached:		
quantities used and i	g depths, centralizers top of cement, perforat g depth, location and t	and/or turbolizers and ted intervals. tubing s	location thereof.
b. Plat showing the loca	ation of all wells on a	applicant's lease, all rators of all leases of	offset wells on offset fsetting applicant's leas
c. Electrical log of the and intervals of perf	e well or other accepta Foration indicated them		bottoms of producing zone not available at the

NOTE: If the proposed multiple completion will result in an unorthodox well location and/or a non-standard proration unit in one or more of the producing zones, then separate application for approval of the same should be filed simultaneously with this application.

Title

I hereby certify that the information above is true and complete to the best of my knowledge


Superintendent


SUPERVISOR DISTRICT 第 3

8 1982

## BAKER OIL TOOLS, INC.

SERVING THE WORLD Basin Dakota DATE 10-6-82 689 M LEASE Breech C Blanco Mesa Verde -9 5/8" 32.40 Casing cemented 262' to surface with 250 sacks. -5 1/2" 15.5 & 17# Casing set at 7600'. Cemented in two stages with 980 sacks. -1 1/4" 2.3# IJ Tubing set at 5440' for Mesa Verde Production. - Mesa Verde Perforations 5200 to 5440. \_Baker Model "R" Double Grip Packer set at 5755' - 1 1/4" 2.3# IJ Tubing set at 7515' for Dakota Production. Tocito perforations 6812 to 6826 squeezed with 100 sacks Neat cement. Tested after drilling out with 2000# Held OK. Dakota Per forations 7293-7524





7600'





Township 26 North , Range 6 West , County Rio Arriba , State New Mexico ,

Caulkins Oil Company Breech C 689-M

Unit L Section 12 26 North 6 West

Caulkins	Caulkins	Caulkins
Caulkins	Caulkins	Tenneco
	•	TD 3
11	TD 144	_
1		
	<b>№</b> 689M	
⊙ MD 685E	©  MD 689E	O PD 1
	100072	
Caulkins	Caulkins	Tenneco
	G	<u> </u>
D 244	CMD 248E	0
14	13	CD 1E 18
		16