

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 041

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Puerto Chiquito

9. WELL NO.

6-6

10. FIELD AND POOL, OR WILDCAT

Puerto Chiquito

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6, T-26N, R-1E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7319' RKB

12. COUNTY OR PARISH

13. STATE

Rio Arriba New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Present Status

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1- 7-64 TD 3642'. 4-hour bailing test recovered 1½ gallons muddy water.
- 1- 9-64 TD 3804'. Slight show of gas and rainbow of oil.
TD 3808'. Picked up water. Started bailing.
- 1-10-64 Bailed total of 77 barrels water at approximate rate of 100 barrel per bailer. Fluid level 2600'. Shut down. After being shut down 45 minutes, had 150' of fill-up.
- 1-11-64 Bailing water from 2600'. Bailed approximately 100 barrels in 22 hours.
- 1-13-64 Plugged back with 10 sacks frac sand to 3768'. Dumped 4 sacks calseal, approximately 90 gallons slurry. No apparent fill-up. Dumped 2 sacks calseal, approximately 18 gallons slurry. No apparent fill-up.
- 1-14-64 Plugged back to 3748' with calseal. Bailed hole down to 2223'. In 45 minutes had fill-up of 4' of water.
- 1-16-64 Bailed water down to 3648'.
- 1-17-64 Bailed hole dry. Filled hole with 157 barrels oil to protect formation.
- 10-19-64 Shut down waiting on orders.

18. I hereby certify that the foregoing is true and correct

SIGNED

Albert R. Green

TITLE

Vice-President

DATE

10-19-64

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.