NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

			EM WEXICO PACKI			Well	
	Aztec Oil & G	as Company	Lea	se <u>Jicarill</u>	a 101	No• #1	
cation	A Sec. 1	Two. 26 1	North Rge	4 West	County	Rio Arriba	
werr: our		1 ,,,,,	Type of Prod.	Method of	Prod.	Prod. Medium (Tbg. or Csg.)	
	Name of Reser	voir or Pool	(Oil or Gas)	(Flow or Art	t. Litt)	(Tog. or Csg.)	
1110101011	apacito Pictu	red Cliff	Gas	Flow		Casing	
wer mpletion B	lanco Mesaver		Gas	Flow		Tubing	
			LOW SHUT-IN PRE			Stabilized?	
per Hour, da	ate in 9-17-7	Length C	of c-in 72 Hour	s osig	7	(Yes or No)	
wer Hour. da	ate		of :-in 72 Hour	Si press.	0	Stabilized?	
mpl Shut-	ate in 9-17-7	7 time shut	-in /2 Hour	S psig	0	(Yes or No)	
mmerced at	(bour, date)*	9-	20-77	Zone prod	ucing (Uppe	er or Lower): Uppe	
Time	Lapsed time	Pres	sure	Prod. Zone	Ren	narks	
our, date)	since*	Jober Compt.	Lower Compl.	Temp.	1001		
9-18-77		745	0				
9-19-77		751.	0				
9-20-77		754	0				
9-21-77	24 Hours	245	0				
9-22-77	48 Hours	245	0				
roduction ra	te during tes	st		**	0	our con	
			Bbls. in_thru (Orifice of	Hrs. Meter):	GP	avGon	
as:		MID-T	EST SHUT-IN PRE	DOULD DETT			
oper Hour, d	late	Length	of	SI press.		Stabilized? (Yes or No)	
Compl Shut-in time shu			t-in	SI press.		Stabilized?	
Lower Hour, date Length Compl Shut-in time shu			t-in	psig		1 /	
			FLOW TEST NO). 2	luaina (IInn	er or Lower):	
	(hour, date)	÷× Proc	euro	Prod. Zone	racing (opp	er or hower).	
Time Lapsed time		Pressure Upper Compl. Lower Compl.				emarks	
nour, austr							
	 				······································		
roduction r	ate during te	st	<u></u>		0	COR	
il:	BOPD b	ased on	Bbls. in_	Hrs.	Grav.	GOR	
as:		_MOFPU; Tested	thru (ortitee	01 H00017			
EMARKS:							
haraby car	tify that the	information	harein contains	d is true and	complete t	to the best of my	
nowledge.				or <u>Aztec C</u>	. ,	\	
.pproved:	-	19	Operac		1/1/		
New Mexico	Oil Conservat	ion Commissio	n By				
	El II i a madri		Title_	Distric	t Producti	on Manager	
Citle			Date	Septemb	per 29, 197	7	
						00T 11 1977	
						Oll Other Park	
						OIL COR. COR.	
-						The second second	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commerce when both zones of the dual completion are shat-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided bowever, that they need not remain shut-in more than seven days.
- 4. For Ylow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains substant. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shuttin, in accordance with Paragraph 3 above.
- 6. Flow Twst No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in gaile the zone which was previously shut-in is produced.

= PC

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals 1.3 follow 1.3-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow poriod (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Commission on Northwest New Mexico Packer Leakage Test Form Revised 11-1-58, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test Form.

·- ·				
. n .				
- ; •				
,				****************