

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

CONTRACT #153

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

JICARILLA APACHE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

JICARILLA "J"

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

BASIN DAKOTA

11. SEC. T. R. M., OR BLK. AND
SURVEY OR AREA

SEC. 26, T-26N, R-5W,
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

RIO ARriba NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL ☐ WELL GAS ☒ WELL ☒ OTHER

2. NAME OF OPERATOR

SOUTHERN UNION PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 808, FARMINGTON, NEW MEXICO 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

790 FT. FROM NORTH LINE AND 1980 FT. FROM EAST LINE

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6576 FT. R.K.B.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO :

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF :

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) SUPPLEMENTARY HISTORY

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. DRILLED 7-7/8" HOLE TO TOTAL DEPTH OF 7525 FT. R.K.B. REACHED T.D. JULY 16, 1967.
2. RAN 231 JTS. OF 4-1/2", 10.50#, J-55 CSG. LANDED AT 7524 FT. R.K.B. CEMENTED 1ST STAGE W/650 CU.FT. OF 1-1 DIAMIX CMT. PLUG DOWN 8:00 A.M. 7/17/67. SET STAGE COLLAR UNDER MESAVERT DE AT 5440 FT. R.K.B. CEMENTED W/700 CU.FT. OF HYS "C" 400 CEMENT. PLUG DOWN 9:00 A.M. 7/17/67. SET STAGE COLLAR UNDER PICTURED CLIFFS AT 3189 FT. R.K.B. CEMENTED W/1400 CU.FT. HYS "C" 400 CEMENT. PLUG DOWN 11:15 A.M. 7/17/67.
3. MOVED IN AND RIGGED UP COMPLETION UNIT 7/31/67.
4. RAN 1-1/2" E.U.E. TBG. DRILLED STAGE COLLARS AT 3189 FT. AND 5440 FT. R.K.B. CLEANED OUT TO P.B.T.D. OF 7488 FT. R.K.B.
5. PRESSURE TESTED CASING TO 4000 PSI FOR 15 MIN. TEST OK. SPOTTED 500 GAL. OF 7-1/2% REGULAR ACID.
6. RAN GAMMA-RAY CORRELATION LOG AND CEMENT BOND LOG.
7. PERFORATED 1ST STAGE DAKOTA 2/FT. 7342-7360 FT., 1/FT. 7378-7384 FT., 1/FT. 7388-7396 FT., 1/FT. 7432-7446 FT.. SAND WATER FRAC PERFS W/50,000# 20-40 SAND, 20,000# 10-20 SAND, 1000# 12-20 GLASS BEADS AND 85,680 GALLONS OF 0.8% KCL WATER.
8. SET 4-1/2" MODEL P-1 BRIDGE PLUG AT 7265 FT. R.K.B. TEST PLUG 4000#. TEST OK.
9. PERFORATED 2ND STAGE DAKOTA 2/FT. 7214-7222 FT., 2/FT. 7224-7232 FT. SAND WATER FRAC PERFORATIONS W/15,000#, 20-40 SAND; 10,000# 10-20 SAND; 1,000# 12-20 GLASS BEADS AND 30,660 GAL OF 0.8% KCL WATER.
10. RAN TUBING AND CLEANED OUT TO P.B.T.D. OF 7488 FT. R.K.B.
11. RAN 227 JTS. OF 1-1/2" E.U.E., 2.90# TBG. LANDED AT 7314 FT. R.K.B.

(CONTINUED)

18. I hereby certify that the foregoing is true and correct

Original signed by

SIGNED GILBERT D. NOLAND, JR.

TITLE DRILLING SUPERINTENDENT

DATE AUGUST 14, 1967

GILBERT D. NOLAND, JR.

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-385229
967-851

12. COMPLETED WELL AUGUST 3, 1967.

12. COMPLETED WELL AUGUST 3, 1967.

