

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget (Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Contract #105

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla "A"

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT
Ignacio Pineda Cliffs

11. SEC., T., R., OR S.E.K. AND
SURVEY OR AREA
Sec. 14, T-26N, R-4W,

N.M.P.M.

12. COUNTY OF **PIÑON** 13. STATE

New Mexico

1. OIL ☐ WELL GAS ☒ WELL OTHER ☐

2. NAME OF OPERATOR

Southern Union Production Company

3. ADDRESS OF OPERATOR

P. O. Box 806, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface **790 ft./North line & 1670 ft./West line.**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6933 ft. R.K.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) **Spudding** ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 13-3/4" surface hole 12 Noon May 18, 1968. Drilled to total depth of 320 ft. R.K.B.
2. Run 10 jts., 10-3/4", 40.50#, K-40 surface casing. Landed at 314 ft. R.K.B. Cemented w/400 sacks regular cement w/2% Calcium Chloride and 1/4% flo-cella/sk. Plug down 4:00 P.M. May 19, 1968. Cement circulated to surface.
3. Ripped up and pressure tested surface casing and blowout preventer to 1000 psi for 15 minutes. Test OK.
4. Drilled out from under surface casing w/7-7/8" hole on May 20, 1968.



U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

Original signed by
GILBERT D. NOLAND, JR.

SIGNED

Gilbert D. Noland, Jr.

TITLE

Drilling Superintendent

DATE

June 3, 1968

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229

9 87 - 9 51

