

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. Contract No. 153	
2. NAME OF OPERATOR Southern Union Production Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache	
3. ADDRESS OF OPERATOR P. O. Box 808, Farmington, New Mexico 87401		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1830/South line & 1140/East line.		8. FARM OR LEASE NAME Jicarilla "J"	
14. PERMIT NO.		9. WELL NO. 13	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6703 ft. Ungraded ground level		10. FIELD AND POOL, OR WILDCAT South Blanco Pictured Cliff Basin, Dakota	
		11. SEC., T., R., OR BLK. AND SURVEY OR AREA Sec. 36, T-26N, R-5E, N.M.P.M.	
		12. COUNTY OR PARISH San Arriba	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Spudding ☒	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 13-3/4" surface hole at 10:00 P.M. July 9, 1968. Drilled to T.D. of 325' A.B.
2. Ran 10 jts. of 10-3/4", 32.75', H-40 surface casing. Landed at 309 ft. A.B. Cemented w/225 lbs. regular cement w/2% Calcium Chloride and 1/4" Flo-Calc/sec. Plug down 5:00 A.M. July 10, 1968. Cement circulated to surface.
3. Hipped up and pressure tested surface casing and blowout preventer to 1000 psi for 10 minutes. Test OK.
4. Drilled out from under surface casing with 9-7/8" hole on July 10, 1968.



RECEIVED
JUL 11 1968
U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED GILBERT D. NOLAND, JR. TITLE Drilling Superintendent DATE July 15, 1968
Gilbert D. Noland, Jr.

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of well; and date well site conditioned for final inspection looking to approval of the abandonment.