

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Approved,
Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Mobil Oil Corporation	8. FARM OR LEASE NAME Mobil Jicarilla D.
3. ADDRESS OF OPERATOR Box 1652, Casper, Wyoming 82601	9. WELL NO. 15
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650' North of South Line & 990' West of East Line Sec. 23, T26N, R3W, Rio Arriba County, New Mexico	10. FIELD AND POOL, OR WILDCAT Gavilan-Pictured Cliffs
14. PERMIT NO.	11. SEC., T., R., M., OR BEE, AND SURVEY OR TARRA NE SE (1) Sec. 23, T26N, R3W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GR 7316'	12. COUNTY OR PARISH, STATE Rio Arriba New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

FULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) 11-20 thru 11-27-68 Weekly Rpt

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-20-68 Spudded hole at 2:00 p.m. Cemented 7" 23# J55 casing at 270' in 9" hole w/100 sacks regular cement containing 3% CaCl_2 . Plug down at 8:30 p.m. Installed casing head, BOP WOC & prepared to drill ahead.
11-21-68 Drilling 6 1/2" hole at 715'
11-22-68 Drilling sand & shale at 2130'
11-23/25-68 Drilled 2130'-3745'
11-26-68 TD 3892'. Cemented 3 1/2" csg. at 3891' in 6 1/2" hole w/50 sacks regular cement, bumped plugs at 1:30 a.m. Released rig.
11-27-68 Moved out rotary rig



18. I hereby certify that the foregoing is true and correct

SIGNED

John Hamlin

(This space for Federal or State office use)

TITLE Supervisor General Acctg.

DATE

12-18-68

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY

TITLE

*See Instructions on Reverse Side