

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078477

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Nordhaus

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 17, T25N, R7W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N. M.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

Box 234, Farmington, N. M. 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1650' fs1, 1850' fw1

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, GR, etc.)

6465' Gr.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

4/17/69

Spud 11 1/4" hole with shot hole rig - drill to 92' - ran 2 jts.  
8 5/8" O.D., 20# limited service csg. set at 91' cemented with 75  
sx. Class "A" 2% Cacl.

4/22/69

T.D. 2310'. Ran Wellex Induction-Electric log and Gamma Ray-Density-  
Caliper log. Ran 68 jts. 4 1/2" O.D., 9.5#, K-55, 8R, ST&C-CF&I csg.  
T.E. 2300.94' set at 2309' R.K.B. cemented with 75 sx. Class "A" 8%  
gel. plus 75 sx. Class "A" with 7 1/2# salt per sx. P.O.B. 1:45 pm,  
4/21/69. Good mud circulation while cementing, followed plug with  
300 gal. Acidic Acid.

18. I hereby certify that the foregoing is true and correct

SIGNED J. A. Nyeau (J & J)TITLE EngineerDATE 7/14/69

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

\*See Instructions on Reverse Side

RECEIVED

JUL 15 1969

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.