

Form 9-351
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SE 078477

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hordhaus

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Ballard P.C.

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 20, T25N, R7W

12. COUNTY OR PARISH 13. STATE

Rio Arriba N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

Jerome P. Hollugh

3. ADDRESS OF OPERATOR


Box 234, Farmington, N. M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1850' fs1 790' fw1

14. PERMIT NO.

15. ELEVATIONS (SHOW whether ft., m., or etc.)



16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/18/69

Spool 11 1/4" hole, drilling to 92' - ran 2 jts. & 5/8" O.D., 20#, limited service cement at 87' R.K.B. cemented with 75 sx. Class "A" 25 Cact, good cement to surface.

4/27/69

I.O. 2100'. 100' hole, drilling to 2204' - ran 10 jts. 4 1/2" O.D., 9.5#, K-55, 20, S-10 - cemented with 75 sx. Class "A" 25 Cact, good cement to surface. Cemented with 75 sx. Class "A" 25 Cact, good cement to surface. P.O.B. 2200 p.m., 4/27/69. Plug 1700 gal. Acidic Acid - good mud returns while cementing. 100' test rotary rig.

18. I hereby certify that the foregoing is true and correct

SIGNED Original signed by T. A. Dugan

TITLE Engineer

DATE 8/6/69

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

AUG 8 1969

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.