

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2002 FEB 20 PM 4:16

CFO REGISTRATION UNIT

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

800' FSL, 1060' FWL, Sec. 26, T-26-N, R-6-W, NMPM

5. Lease Number
SF-0792666. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Vaughn #99. API Well No.
30-039-2023510. Field and Pool
Otero Chacra11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment

Type of Action

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other -☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection

13. Describe Proposed or Completed Operations

1-29-02 MIRU. (Bob Vigil, BLM on location). ND WH. NU BOP. TIH w/2 7/8" CIBP, set @ 3470'. TOOH. TIH, tag CIBP @ 3470'. Establish circ w/20 bbl wtr. PT csg to 500 psi, failed. Plug #1: pump 21 sx Class "B" neat cmt inside csg @ 2708-3470' to cover Chacra interval. TOOH to 2700'. Plug #2: pump 22 sx Class "B" neat cmt inside csg @ 1908-2708' to cover Pictured Cliffs, Fruitland & Kirtland formations. TOOH. WOC. SDON.

1-30-02 (Bob Vigil, BLM on location). TIH, tag TOC @ 2124'. Load csg w/wtr. PT csg to 500 psi, failed. Plug #3: pump 14 sx Class "B" neat cmt inside csg @ 1616-2124' to cover Ojo Alamo formation. TOOH. WOC. TIH, tag TOC @ 1790'. (175' above Ojo Alamo). TOOH. TIH, perf 2 sqz holes @ 898'. TOOH. TIH w/cmt retainer, set @ 828'. Establish injection. Plug #4: pump 29 sx Class "B" neat cmt outside csg below cmt retainer @ 798-898'. Pump 8 sx Class "B" neat cmt above cmt retainer inside csg @ 611-828' to cover Nacimiento formation. TOOH. SDON.

1-31-02 PT csg to 500 psi, failed. TIH, tag TOC @ 630'. TOOH. TIH, perf 2 sqz holes @ 177'. Establish circ down csg & out bradenhead w/10 bbl wtr. Plug #5: pump 60 sx Class "B" neat cmt down 2 7/8" csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Found cmt 20' down in 2 7/8" csg & down 25' in annulus. Fill csg & annulus w/15 sx Class "B" neat cmt. Install dry hole marker w/5 sx Class "B" neat cmt. RD. Rig released.

Well plugged and abandoned 1-31-02.

14. I hereby certify that the foregoing is true and correct.

Signed
no

Title Regulatory Supervisor

Date 2/19/02

(This space for Federal or State Office use)

APPROVED BY

Title

Date

FOR RECORD

CONDITION OF APPROVAL, if any:

25 2002

SWS OFF: