

& NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION OFFICE
AZTEC DISTRICT OFFICE
1000 RIJO BRAZDE ROAD
AZTEC HM 87410
(800) 334-6170 FAX: (800) 334-6170
http://icompression.nu.us/cod/Clourer Rifsdoorie, htm.

This form is not to be used for reporting packer lealings tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

| Operator | CON | OGO INC | Lease Nan | neJ] | CARILLA | A | Well No_13 (PM D) | |
|---------------------|-----------------------------|------------------|------------------|-------------------------------|-------------------|-----------------------|-------------------------------|--|
| Location of \ | Well:Unit Letter | E_Sec_1 | 3 Twp_26 | Rge_ ⁰⁴ _ | API # 30-(| o <u>39223</u> | 33900 | |
| | NAME OF RESE | RVOIR OR POOL | | TYPE OF PROD. (Oil or Gas) | | F PROD. .rt. Lift) | PROD.MEDIUM (Tbg. or Csg.) | |
| Upper Completion | PICTURED ', MESA VERD | | G.P. | GAS | | OW | TBG. | |
| Lower Completion | DAKOTA | | G <i>I</i> | GAS | | OW | TBG. | |
| | | PRE | -FLOW SHUT-I | N PRESSUR | F DATA | | | |
| Upper | Hour, date shut-in | | Length of time | | SI press. Pslg | | Stabilized? (Yes or No) | |
| Completion | ZONE TEMP. SHUT IN | | Г | | 251 | ÷ | NO | |
| Lower Completion | Hour, date shut-in 09-24-00 | | | Length of time shut-in 3-DAYS | | | Stabilized? (Yes or No) NO | |
| | | | | ST NO. 1 | | | | |
| Commenced at (| hour, date)* | 09-27-00 | | Zone producing | (Upper or Lower): | t | JPPER | |
| TIME (hour,date) | LAPSED TIME SINCE* | | SURE | TEMP. | | REMARKS | | |
| | | Upper Completion | Lower Completion | | | | | |
| 09-25-00 | | 251 | 208 | 0C 21 28 20 S | вотн | BOTH ZONES SHUT IN | | |
| 09-26-00 | 2-DAYS | 251 | 229 | Clarico Ca M | ВОТН | ZONES | SHUT IN | |
| 09-27-00 | 3-DAYS | ₹251 | 229 | 7 | BOTH | ZONES | SHUT IN | |
| 09-28-00 | 1-DAY | 150 | 229 | DEC 2000 | UPPE | R ZONE | FLOWING | |
| 09-29-00 | 2-DAYS | 150 | 229 🕾 (| NE CONVEC | | R ZONE | FLOWING | |
| Production ra | Le during test | BOPD based | | DIST. 3 | Hours | Gra | iv. GOR | |
| Gas: | | | PD; Tested thru | | | | VOON | |
| | | MID | -TEST SHUT-IN | N PRESSUR | E DATA | | - | |
| Upper Completion | Hour, date shut-in | | 1 | Length of time shut-in | | | Stabilized? (Yes or No) | |
| Lower Completion | Hour, date shut-in | | Length of time | Length of time shut-in | | | Stabilized? (Yes or No.) | |

(Continue on reverse side)

FLOW TEST NO. 2

| Commence | d at (hour, date)* | ·• | | Zone producing (Upper or Lowr): | | | |
|--------------------------------------|---------------------|-------------------|--------------------------|---------------------------------|----------------------|-------------|--|
| TIME (hour,date) | LAPSED TIME | PRESS | URE | PROD. ZONE | REMARKS | | |
| | Since | Upper Completion | Lower Completion | | NEMARAS | | |
| | | | | | | | |
| | ļ | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | ! | | | |
| Gas: Remarks: | | Dased onMCFP | Bbls D:Tested thru (C | inHour orfice or Meter): | sGravGOR | | |
| hereby certi | | nation herein con | tained is true and | i complete to the | bes of my knowledge. | | |
| Approved191919 | | | _ Operator_ | | DNOCO INC | New | |
| OFFICIAL SIGNED BY CHARLE TO PRESENT | | | Rv | ~1 | ely Ebert | | |
| | AND COMPANY OF LIVE | APLE T. PROPERTY | <u> </u> | ahu | ag cover | | |
| Ву | | ARLET. MERRY | | | PRODUCTION SUPT. | | |

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion
 are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain
 shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of
- a pipeline connection the flow period shall be three hours.

 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in

accordance with Paragraph 3 above.

 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).