

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

<p>1. Type of Well GAS</p> <hr/> <p>2. Name of Operator MERIDIAN OIL</p> <hr/> <p>3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700</p> <hr/> <p>4. Location of Well, Footage, Sec., T, R, M 990' FSL, 800' FWL, Sec. 36, T-26-N, R-6-W, NMPM, Rio Arriba County</p>	<p>API # (assigned by OCD) 30-039-20539</p> <p>5. Lease Number</p> <p>6. State Oil&Gas Lease # E-291-49</p> <p>7. Lease Name/Unit Name Johnston A</p> <p>8. Well No. 14</p> <p>9. Pool Name or Wildcat Otero Chacra</p> <p>10. Elevation:</p>
---	---

RECEIVED
JUL 19 1996
OIL CON. DIV.
DIST. 3

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

6-25-96 MIRU. ND WH. NU BOP. TIH, tag fill @ 3450'. Plug #1: pump 35 sx Class "B" cmt @ 2200-3450'. TOOH to above cmt. Reverse circ. WOC. TIH. SDON.

6-26-96 TIH, tag TOC @ 2588'. Pump 11 sx Class "B" cmt @ 2200-2588'. Reverse circ. TOOH. TIH, perf 4 sqz holes @ 2165'. TOOH. TIH w/cmt retainer, set @ 1900'. Could not pump through cmt retainer. TOOH. SDON.

6-27-96 TIH, latch top of cmt retainer, TOOH. TIH, tag cmt retainer, punch hole in top of cmt retainer. TIH w/pkr, set @ 1785'. Establish injection. Plug #2: pump 100 sx Class "B" cmt below cmt retainer @ 1900-2165', pump 20 sx Class "B" cmt above cmt retainer to 1800'. TOOH w/pkr. TIH, tag TOC @ 1794'. TOOH to 320'. Perf 2 sqz holes @ 320'. Establish circ down csg & out bradenhead. Plug #3: pump 125 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. SDON.

6-28-96 PT plug #3, OK. ND BOP. Cut off WH. Pump 5 sx Class "B" cmt to fill csg. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 6-28-96.

SIGNATURE *[Signature]* Regulatory Administrator July 16, 1996

(This space for State Use)

Approved by *[Signature]* Title Deputy O&G Inspector Date 7-16-96