

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. CONTRACT #100
2. NAME OF OPERATOR SOUTHERN UNION PRODUCTION COMPANY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME JICARILLA APACHE
3. ADDRESS OF OPERATOR P. O. Box 808, Farmington, New Mexico 87401	7. UNIT AGREEMENT NAME JICARILLA
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 915 FT. FROM THE NORTH LINE & 860 FT. FROM THE EAST LINE.	8. FARM OR LEASE NAME JICARILLA
14. PERMIT NO.	9. WELL NO. 13
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7214 Ft. Ground Level	10. FIELD AND POOL, OR WILDCAT TAPACHO PICTURED CLIFFS
	11. SEC. T., R., S., OR OTHER AND SURVEY OR AREA SEC. 32, T-26N, R-3W
	12. COUNTY OR PARISH N.M.P.M.
	13. STATE NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) SPUDDING ☒	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. SPUDDED 12-1/4" SURFACE HOLE AT 11:30 P.M. AUGUST 14, 1973. DRILLED TO TOTAL DEPTH OF 237 FT. R.K.B.
2. RAN 7 JOINTS OF 8-5/8", 24.0#, K-55 SURFACE CASING. LANDED AT 234 FT. R.K.B. CEMENTED WITH 150 SACKS OF CLASS "A" CEMENT WITH 2% CALCIUM CHLORIDE. PLUG DOWN AT 10:00 A.M. AUGUST 15, 1973. CEMENT CIRCULATED TO SURFACE.
3. NIPPLED UP AND PRESSURE TESTED SURFACE CASING AND B.O.P. TO 1000 PSI FOR 10 MINUTES. TEST OK.
4. DRILLED OUT FROM UNDER SURFACE CASING WITH 7-7/8" HOLE ON AUGUST 16, 1973.

18. I hereby certify that the foregoing is true and correct

Original signed by
SIGNED GILBERT D. NOLAND, JR. TITLE DRILLING SUPERINTENDENT DATE SEPT. 14, 1973
GILBERT D. NOLAND, JR.
(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

SEP 17 1973

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.