

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1450' FNL, 820' FEL, Sec. 27, T-25-N, R-7-W, NMPM

5. Lease Number  
SF-078878

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

Canyon Largo Unit

8. Well Name & Number  
Canyon Largo U #247

9. API Well No.  
30-039-20896

10. Field and Pool  
Ballard Pict Cliffs

11. County and State  
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

3-20-02 MIRU. ND WH. NU BOP. PT BOP. TIH w/gauge ring to 2615'. TOO. TIH w/2 7/8" CIBP, set @ 2610'. TOO. TIH, tag CIBP @ 2610'. Load hole w/22 bbl wtr. PT 2 7/8" csg to 500 psi, failed. Establish circ. Plug #1: pump 25 sx Class "B" neat cmt inside csg @ 1702-2610' to cover Pictured Cliffs, Fruitland, Kirtland & Ojo Alamo interval. TOO. WOC. SDON.

3-21-02 (Jim Ruybalid, BLM was on location). TIH, tag TOC @ 1994'. Establish circ. PT 2 7/8" csg to 500 psi, failed. Plug #2: pump 12 sx Class "B" neat cmt w/2% calcium chloride inside 2 7/8" csg @ 1559-1994' to cover Ojo Alamo interval. TOO. WOC. TIH, tag TOC @ 1728'. TOO. TIH, perf 2 sqz holes @ 320'. Establish circ down csg & out bradenhead w/20 bbl wtr. Circ bradenhead clean. Plug #3: pump 143 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt out bradenhead. WOC. ND BOP. Cut off WH. Found cmt down 20' in 2 7/8" csg. Pump 15 sx Class "B" neat cmt to fill 2 7/8" csg. Install dry hole marker w/5 sx Class "B" neat cmt. RD. Rig released.

Well plugged and abandoned 3-21-02

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Ottman for Title Regulatory Supervisor Date 4/16/02  
no

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

FOR RECOR