ŀ	ϵ_{i}	411	9-331	
ŧ	M	a v	1963	١

UNITED STATES SUBMIT IN TRIPLICATE* Other instructions on recognition on recognition of the INTERIOR (Other instructions on recognition) 5. Lease Designation and Sectal No.

GEOLOGICAL	SF078878	SF078878				
SUNDRY NOTICES AND I (Do not use this form for proposals to drill or to Use "APPLICATION FOR PERM	6. IF INDIAN, ALLA	OTTEE OR TRIBE NAME				
1. OIL GAS (V)		7. UNIT AGREEMENT NAME				
WELL WELL A OTHER	_	Canyon Largo Unit				
2. NAME OF OPERATOR El Paso Natural Gas Co.	[_	8. FARM OR LEASE NAME Canyon Largo Unit				
3. ADDRESS OF OPERATOR	9. WELL NO.					
P. O. Box 990, Farmington, NM 87	256	256				
 LOCATION OF WELL (Report location clearly and in accor See also space 17 below.) 	10. FIELD AND POO	•				
At surface 1520'S, 1760'W	Basin Dako					
1320 0, 1700 N			Sec. 27, T N M.P.M	-25-N, R-7 W		
14. PERMIT NO. 15. ELEVATIONS (DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE				
690	69' GL		Rio Arriba	New Mexico		
Check Appropriate Box	To Indicate	Nature of Notice, Report, o	or Other Data			
NOTICE OF INTENTION TO:			SEQUENT REPORT OF:			
TEST WATER SHUT-OFF PULL OR ALTER CAS	ING	WATER SHUT-OFF	X	ING WELL		
FRACTURE TREAT MULTIPLE COMPLET	E	PRACTURE TREATMENT	<u> </u>	NG CASING		
SHOOT OR ACIDIZE ABANDON*	.	SHOOTING OR ACIDIZING	ABANDO	NMENT*		
REPAIR WELL CHANGE PLANS		(Other) (Note: Report res	sults of multiple complet	tion on Well		
(Other) 17. DESCRIBE PROFOSED OR COMPLETED OPERATIONS (Clearly services the description of the complete of th	tate all pertin	ent details and give partinent de	ompletion Report and Lo	g form.)		
proposed work. If well is directionally drilled, give nent to this work.) *	subsurface lo	cations and measured and true ve	rtical depths for all ma	rkers and zones perti-		
04-04-75 TD 7190'. Ran 165 joir casing; 7178' set at 71 at 5200'. Cemented fin 1486 cu. ft. cement.	190'. Fi rst stage WOC 18 he	loat collar set at 7 e with 325 cu. ft. coours. Top of cement	175'. Stage to ement; second s	ool set stage with		
10-08-75 PBTD 7175'. Tested casing to 4000#OK. Perf'd 6932', 6944', 6956', 6966', 7018', 7040', 7068' with 1 shot per zone. Frac'd with 45,295#40/60 sand and 58,060 gallons treated water. Dropped no ball sets Flushed with 5520 gallons water.						
	,					
	/ nrT	10 9 147 5		4		
	QUI	60 1010				
	100.3	COM. COM.				
	es e	137. 3				
8. I hereby certify that the foregoing is true and correct						
SIGNED A. J. Stices	TITLE	Drilling Clerk	DATE O	ctober 20, 1975		
(This space for Federal or State office use)						
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE			