## INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 23, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formational has been an analysis, should be attachments of the form and time time and the content and the form an

should be listed on this form, see item 35.

Hem 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State

from 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. Here 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and 24 above.) or Federal office for specific instructions.

33: Submit a separate completion report on this form for each interval to be separately produced.

Cemented thru shoe @ 3400, with 250 sacks.

Alamo 2622 27244 Water send  Pictured thiffs 3194 (3300 Gas sand  Deviation Test (degrees)  971 1045 1650 2314 2741 3311	HRAD TRALESLE TVARIALIN HAPPO	TESTED CARTION US	SITY AND CONTE	SHOW ALL BUTCHAST ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DESCRIP STEAR TESTS, CUSHIQN USED, CHIS TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES DRIVEN OF THE SECONDARY OF THE SECON	 S. NAME	GEOLOGIC MARKERS	Ō
2622 19704 Water Cas se Cas 3194 (degrees)  Deviation Test (degrees)  971 260 2741  3740  3740  3740  3741					N'A	N. E	NE
tation Test (degrees)  intion Test (200 3/40)  1 1 2/40  1 1 2/40	Alamo	2622	100	er T	 		
ation Test	Pictured &1	iffs 31%	3320	ည က			** !
ation Test							
	Deviat	ion Test		(degrees)			
	971 1045 1660		- (	2000			
	2741 2741 3311	•		1°/4°			

U Ş.