Form 9 331 (May 1963)

## UNITED STATES DEPARTMENT OF THE INTERIOR CONTROL OF THE PROPERTY OF THE PROP

SUBMIT IN TRIPLICATES\*

Form approved Budget Bureau No. 42 R1424. 5, LEASE DESIGNATION AND SERIAL NO. Jicarilla Apache Cont #119

> DATE . .

117114	ı Oı	1 1	IL IMILITION Verse side)	
	00104		CHONEN	

GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT." for such proposals.) Jicarilla Apache 7. UNIT AGREEMENT NAME GAB WELL WELL OTHER 8. FARM OR LEASE NAME 2. NAME OF OPERATOR Jicarilla 119 N Northwest Production Corp. 3. ADDRESS OF OPERATOR 9. WELL NO. 5A Box 990, Farmington, New Mexico 87401 LOCATION OF WELL (Report location clearly and in accordance with any Smite requirements.\* See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 1630'N, 1500'W Sec. 6, T-26-N, R-4-W, N.M.P.M. 12. COUNTY OR PARISH 13. STATE 14. PERMIT NO. 15. ELEVATIONS (Show whether DF 7198' GL Rio Arriba <u>lNew Mexico</u> 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: REPAIRING WELL TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF X. ALTERING CASING MULTIPLE COMPLETE FRACTURE TREATMENT FRACTURE TREAT SHOOTING OR ACIDIZING ABANDONMENT\* ABANDON\* SHOOT OR ACIDIZE CHANGE PLANS REPAIR WELL (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \* TD 4237'. Ran 100 joints 7", 23#, KS & NQS intermediate casing, 4225' set at 4237'. Cemented with 684 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2300'. TD 6477'. Ran 76 joints 4 1/2", 10.5#, KS casing liner, 2402'set 4075-6477'. Float collar set at 6460'. Cemented with 425 cu. ft. cement. WOC 18 hours. PBTD 6460'. Tested casing to 4000#, OK. Perfed 5606', 5621', 5651', 5657', 5691'. 5718', 6099', 6113', 6133', 6141', 6148', 6160', 6168', 6197', 6208', 6228', 6240', 6277' with 1 shot per zone. Fraced with 122,000# 20/40 sand and 08-31-76 121,290 gallons water. No ball sets dropped. Flushed with 8220 gallons water. 18. I hereby certify that the foregoing is true and correct TITLE Drilling Clerk DATE September 1, 1976 SIGNED

(This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY