

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE, SECTION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR HOLCOMB INC.		8. FARM OR LEASE NAME Grevey
3. ADDRESS OF OPERATOR 112 So. Copper Street Dering, N. H.		9. WELL NO. # 4
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2055' FNL x 510' S.W. of Sec. 26		10. SURFACE AND CLOSURE OF WILDCAT E. Puerto Chig. Manco
14. PERMIT NO.		11. SEC., T., R., M. OF BLK. AND SURFACE OR TOWN R. 1 East E 26-26 N-1 E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7023' R		12. COUNTY OR PARISH N.H.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	(Other) ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Due to the highly fractured oil pay encountered at 1978 ft., we submit the following proposal for completion of Grevey #4: Set drillable wire line plug at 1775 ft., topped with 15 ft. cal-seal plug, set with pump bailer. If appropriate plug is unavailable cover pay zone with gravel topped by 25' cal seal plug. Mud up hole. Pull existing 1770 ft of 5 1/2" casing, ream 4 1/2" hole to 6 3/4" from approximately 1740 ft. to cement plug, and run 4 1/2" J-55, 2.50 lb. casing to bottom. Cement with 45 bags cement. Drill cement plugs with cable tools and drill to bottom of pay zone approximately 2005 ft. Completed open hole. We will be ready to start this program as soon as our rig can be converted to a rotary cable tool combination..approximately 2 weeks--9-1-78.



18. I hereby certify that the foregoing is true and correct

SIGNED David H. Green TITLE _____

DATE 8-21-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

DATE _____

*See Instructions on Reverse Side

OK

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

5010-108-847-485