Completion

OIL CONSERVATION DIVISION

2001

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator (CORDILLERA EI	NERGY, INC	·	Lease _	JICARILLA	-	Well No.	CIÀ
ocation	Unit <u>A</u>	_		Twp. <u>.</u>	26NRg	e. <u>4W</u>	API#	30-039-21345
	NAME OF RESERVOIR	OR POOL		TYPE OF PRO			OD OF PROD. or Art. Lift)	PROD. MEDIUM (Tbg. or Csg.)
			+	(Oil or Gas	<u>/</u>	(1,000	01746. =117	
pper	PICTURED CLIFFS			GAS		FLO	FLOW TBG	
ower	MESA VERDE			GAS		FLC	w	TBG
ompetion 1	WEO/ CELLS		DDE 1	FLOW SHUT-IN	DDESS! IDI	= NATA		
				Length of time shut-in	SI press. psig		Stabilized? (Yes or No)	
pper	Hour, date shut-in		ľ	3 days		266 yes		yes
ompletion ower	12/26 Hour, date shut-in			Length of time shut-in		SI press. psig		
ower completion	12/26			3 days		3	yes	
				FLOV	V TEST NO.	1		
ommenced	at (hour, date) *	12/29/01			Zone producin	g (Upper or Lov	wer):	lower
TIME	LAPSED TIME	Р	RESSURE		PROD. ZONE	DEMARKS		C
nour, date)	Since *	Upper Completion		Lower Completion	ТЕМР.		REMARKS	
100.1		csg	tbg	tbg				
12/27		251	246	341	<u> </u>	Both Zo	nes Shut In	
12/28		267	264	382		Both Zones Shut In		
12/29		268	266	385		Both Zones Shut In		
	1 day	268	266	129		Lower Zone Flowing		
12/30	l uay							
12/31	2 days	268	266	129	1	Lower Zone Flowing		
Productio	n rate during test			Ohla is		łours	Grav.	GOR
Oil:	BOPD ba	ased on		Bbls. in		louis		
Gas:		MCFPD: Tested th	Meter)	mETER				
			MID-	TEST SHUT-IN	PRESSURE	DATA		
Upper	Hour, date shut-in			Length of time shut-in		Si press. p	sig	Stabilized? (Yes or No)
Completion				Length of time shut-in	SI press. p	sig	Stabilized? (Yes or No)	

Length of time shut-in

FLOW TEST NO. 2

Commenced	at (hour, date) **			Zono Broducina	(1)			
Time	LAPSED TIME	PRES	SURE	PROD. ZONE	(Upper or Lower):			
(hour, date)	SINCE **		Lower Completion	TEMP.	REMARKS			
	 							
				 				
	<u> </u>			 				
	<u> </u>							
Production	rate during test							
Oil:	BOPD ba	sed on	Bbls. in	Hrs.	Grav GOR			
Gas:	BOPD based onBbls. inHrsGravGORMCFPD: Tested thru (Orifice or Meter):							
Remarks:		<u> </u>	a (a.maa ar Mater).					
I hereby certif	v that the information	herein contained is tru						
	JAN	O O O O	e and complete to tr	e best of my knowl	ledge.			
Approved	- VAIV -	3 2002 ,2001	Opera	tor CØRDILL	ERA ENERGY, INCORPORATED			
New Mexic	Oil Conservation	p.Division		1/ 1	O// 4			
		. याचा विकास स्थापना । विकास सम्बद्धाः	Ву	Kay S. C	Esstein			
Ву			Title	PRODUC	TION TECHNICIAN			
Title	TY OIL & DAS INSTRUCTOR HOLD ON			12/31/01				
			Date	12/01/01				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrubed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak 'was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a dead-weight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-nminute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)