NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

			ADM LINKTOO IMOIN			Well	
	Caulkins O	il Company	Lea	ase <u>Bree</u>	ch B	No193	
ogation							
f Well: Unit	Sec. 7	Twp20_N	Trans of Prod	Method	of Prod	Prod. Medium	
N	Ioma of Dogom	voir or Pool	(Oil or Gas)	(Flow or	Art. Lift)	(Tbg. or Csg.)	
	vame of Reser	VOIR OF FOOT	(OII OI Gas)	(110% 01	MIO. EIIO	(108, 01 000)	
pper ompletion F	ictured Cl	iffs	Gas	Flow		Tubing	
ower	2004204 03						
Completion Chacra		Gas		Flow		Tubing	
JIII DE LOUIN		PRE-FI	LOW SHUT-IN PRE	SSURE DATA			
oper Hour, da	ate	Length o	of	SI pres		Stabilized?	
ompl Shut-in time			t-in	psig SI press.		(Yes or No)	
		, –	Length of			Stabilized?	
mpl Shut-	in	time shu	t-in	psig		(Yes or No)	
	/ <u> </u>	(0.00 sm 10	FLOW TEST NO	· i	coducing (Horse	exxr Lower):	
onmenced at (hour, date)*9:00 am Time Lapsed time			LL-10	Prod. Zone		SEXX. DONO.	
Time nour, date)	Time Lapsed time		Upper Compl. Lower Compl.			Remarks	
9:00 am	STILCE	opper compre	Donor Compac	Temp.			
.0-23-78	24 hrs	375	440	_	Both zone	s shut in	
9:00 am		1				- 	
0-24-78	48 hrs	392	453		Ditto		
9:00 am							
.0-25-78	72 hrs	410	465		PC SI; Ch	acra opened	
9:00 am	0. 3	101	270		Chacra Fl	owi na	
10-26-78	24 hrs	421	270		onacra ri	AMTIR	
9:00 am LO-27-78	43 hrs	434	270		Ditto		
.0=27=70	40 1113	424	~ []				
roduction ra	te during te	st			_	aan	
٠٦.	ROPD ha	esed on	Bbls.in	Hr	sGr	avGOR	
as:]	MCFPD: Tested	thru (Orlilce o	or Meter):_			
		MLD-T	EST SHUT-IN PER	SSUAL DATA		Stabilized?	
	er Hour, date Length			SI press. psig		(Yes or No)	
ompl Shut-in to be be be been been been been been been			time shut-in Length of		SS.	Stabilized?	
ompl Shut-		time shu		psig		(Yes or No)	
ompij birde	111		FLOW TEST NO). 2			
ommenced at	(hour, date)	**		Zone p		er or Lower):	
Time	Lapsed time	Pres	sure	Prod. Zone	D		
hour, date)	since **	Upper Compl.	Lower Compl.	Temp.	<u> </u>	emarks	
					 		
						_	
,	 	+		,			
		<u> </u>			<u> </u>		
				· · · · · · · · · · · · · · · · · · ·			
					; ; ;		
	A - A4 4-		1		<u> </u>		
	ate during te		Bbls. in	hrs.	. Grav	GOR	
11:	BOID C	MCFPD: Tested	thru (Orifice	or Meter):			
a5				·			
EMARKS:							
						to the hoot of mir	
	tify that the	information				to the best of my	
nowledge.			· ·	Caulk	cins Oil Co	mpany	
		10	∪psrati ∕	\	. 1	1	
oproved:	0:1 C A	19 cion Commissio	n p ₁₇	الم . الم . الم	Blance	H	
			11 LY 1	antigra		¥6	
, \	5 Can	•	Title	Produ	action Fore	man	
V V	Cr. Jan	X					
litle)	Date	10-3	J73 .		
. エレエピ							

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- 2. At least 72 hours prior to the commencement of any packer leakage test the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shutin, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above—described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Commission on Northwest New Mexico Packer Leakage Test Form Revised 11-1-58, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may oe reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test form.

