

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

SUNDRY NOTICES AND REPORTS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 3249, Englewood, Co 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

below.)
AT SURFACE: 835' FWL 980' FNL "D"
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: ☐

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*

ABANDON*
(other) Recompletion activities(subsequent)

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☒
☒
☐
☐

squeeze

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*.

9/16/80 MIRUSU Blew down well. NDWH.NUBOP Released pkr & TOH w/tbg and pkr.
SDON. Retainer and 2-3/8" tbg. Set retainer @ 5592

SDON.
9/17/80 TIH w/Baker model K cmt. retainer and 2-3/8" tbg. Set retainer @ 5592'.
RU Halliburton and PT tbg to 2000 PSI. Held OK for 5 mins. Press'd up to 2-3/8"
tbg, 4 1/2" csg, annulus to 1000PSI. Pumped water in to Gallup formation down tbg.
and established rate of 6 BPM @ 4000PSI. Pumped 150sx Class-B cmt. dn tbg.
Average rate: 5BPM @ 1500 PSI. Formation squeezed off @ 2500 PSI. Circ'd hole
clean w/1% KCL water. Pulled tbg to 5273' and spotted 500 gals 7 1/2" DI-HCL over
Mesaverde perms. TOH w/tbg. RU Schlumberger and ran GR/CCL/CBL from 3400-5400'
Bonding was adequate over both Mesaverde and Chacra perms. TOC @ 3894'. Perf'd
Mesaverde w/3-3/8" premium charge gun @ 2 JSPF as follows; 5066-67', 5118-19',
5200-01', 5234-35', 5238-51', 5258-60', 5268-70', 21' 42 holes SDON.
_____ Set @ _____ Ft.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Asst. Div. Adm. Mgr DATE January 29, 1981

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____