

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR Northwest Production Corp.
~~EL PASO NATURAL GAS CO.~~

3. ADDRESS OF OPERATOR
BOX 289, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 810'S, 880'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- CHANGE ZONES
- ABANDON*
- (other)

SUBSEQUENT REPORT OF:

-
-
-
-
-
-
-
-

RECEIVED
NOV 20 1978
U. S. GEOLOGICAL SURVEY

5. LEASE
Jic. Apache Tribal Cont. #152

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jic. Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jicarilla 152W

9. WELL NO.
2A

10. FIELD OR WILDCAT NAME
So. Blanco P.C. - Blanco MV

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec. 5, T-26-N, R-5-W
NMPM

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6575' GL

NOTE: Report results of multiple completion or zone change on Form 9-330.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/3/78: T.D. 3521'. Ran 86 joints 7", 20# K-55 intermediate casing, 3613' set 3521'. Cemented with 207 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2500'.

7/7/78: T.D. 5855'. Ran 60 joints 4 1/2", 10.5# K-55 casing liner, 2613' set 3365-5855'. Float collar set at 5438'. Cemented with 431 cu. ft. cement. WOC 18 hours.

8/6/78: PBTD 5438'. Tested casing to 3500#, OK: 3184-3206, 3214-32, 3240-52 w/20 SPZ. Fraced w/60,000# 10/20 sand and 60,000 gal. water. Flushed w/5400 gal. water. Perfed C.H. and Men. 4853, 4862, 4873, 4879, 4886, 4900, 4908, 4916, 4924, 4932, 4940, 4955, 4962, 5210, 5254, 5262, 5326, 5333, 5340 w/1 SPZ. Fraced w/75,000#

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. P. Busco TITLE Drilling Clerk DATE 11/15/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

