

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
*SUPRON ENERGY CORPORATION*
3. ADDRESS OF OPERATOR  
*P.O. Box 800, Farmington, New Mexico*
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: *840 ft./North & 1110 ft./West line*  
AT TOP PROD. INTERVAL: *Same as above*  
AT TOTAL DEPTH: *Same as above*
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
*Contract No. 100*
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
*Jicarilla Apache*
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
*Jicarilla "D"*
9. WELL NO.  
*17*
10. FIELD OR WILDCAT NAME  
*Blanco Mesaverde*
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
*Sec. 29, T-26N, R-3W  
N.M.P.M.*
12. COUNTY OR PARISH  
*Rio Arriba*
13. STATE  
*New Mexico*
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
*7087 R.K.B.*

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. *Spudded 12¼" surface hole at 7:30 a.m. 8-14-79.*
2. *Drilled 12¼" hole to T.D. of 247 ft. R.K.B.*
3. *Ran 7 joints (230 ft.) of 7-5/8", 26.40#, K-55 casing. Landed at 242 ft. R.K.B.*
4. *Cemented with 200 sacks of class "B" with 3% Calcium Chloride and ¼# cello flakes per sack. Plug down at 4:15 a.m. 8-15-79. Cement circulated to surface.*
5. *Waited on cement for 12 hours.*
6. *Pressure tested csg. to 1000 PSI for 15 minutes. Held OK.*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Kenneth E. Roddy* TITLE *Production Supt.* DATE *August 16, 1979*  
*Kenneth E. Roddy*

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

AUG 17 1979

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.