STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Maxioo

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

_	CONOCO INC					Lesee	Lease		Well TICARILLA No. 22A (PD)			
Operator Location					· · · · · · · · · · · · · · · · · · ·					,	RIO ARRIBA	
of Well: Unit Sec24_ Twp				TYPE OF PROD.		METHOD OF PROD. (Flow or Art. Lift)			PROD. MEDIUM (Tog. or Cog.)			
Upper Completion PICTURED CL				CLIFF	LIFF GAS		FLOW		·	TBG.		
Lower Completion M V				GAS	GAS .		FLOW		TBG.			
						OW SHUT-IN P	RESSURE	DATA				
Upper	Hour, date shul-in				Length of time shut-in		St press. pelg			Stabilized? (Yes or No)		
Completion	10 08 10 97				3-DAYS Length of time shut-in 3-DAYS		174 Si prees. palg 549			NO Stabilized? (Yes or No)		
Competion												
					20.4	FLOW TEST		oducing (Upper	or Lowert:	7.05	P.D.	
		et (hour, dete) *				3_97.		PROD. ZONE		LOWER REMARKS		
	ME , date)	SINC		Up	per Completion	Lower Completion	TEMP.	MP.	NEMOTIVE			
08-1	1-97	1_DA`	Y		166	535	-	·	ВОТ	H ZONES	SHUTIN	
08-12-97		2-DA	YS_	<u> </u>	170	545	ļ		BOTH ZONES SHUT IN			
08-13-97		3-DA	YS		174	549	 		BOTH ZONES SHUT IN			
08-1	08-14-97 1-DAY			175	91	ļ		LOWER ZONE FLOWING				
08-15-97		2-DA	2-DAYS		177	96			LOW	LOWER ZONE FLOWING		
Producti	on rate	during test	•			•						
Oil:			BO	PD ba	sed on	Bbls. is	n	Hours		Grav	GOR	
G25:	·				мсі	FPD; Tested thru	(Orifice	or Meter):				
				•	MID-T	est shut-in p				Tonnilland? W.	ne or Mol	
Upper				Length of time shut-in		SI press. paig			Stabilized? (Yes or No)			
Lower	ower Hour, date shut-in				Length of time of	nut-in	SI press. pelg			Stabilized? (Y	ss or No)	
Completion	<u>'L</u>			•	<u> </u>		•) FA	লিলেলেলেলেলেলেলেলেলেলেলেলেলেলেলেলেলেলেল		

DECEPTION OF

(Continue on reverse side)

OR GOTT

FLOW TEST NO. 2

1 1111111	LAPSED THE			l PROD. ZONE			
(hour, date)	SINCE ##	Upper Completion	Lower Completion	TEMP,	REMARKS		
• · · · · · · · · · · · · · · · · · · ·							
Production rate di	uing test						
Oil:	ВОРІ	D based on	Bbls. in	Hours.	Grav GOR		
Gas:		мсғ	PD: Tested thru	(Orifice or Meter)	₹ 23 W 1		
Remarks:					· · · · · · · · · · · · · · · · · · ·		
							
I hereby certify the	at the informatio	n herein containe	ed is true and con	nplete to the best	of my knowledge.		
Approved New Mexico Oil	OCT. 1.7	1997	_19 0	perator	CONOCO INC		
MEXICO OII	Conservation D	IVISION			SYLVESTER GOMEZ		
Ву	Johnny &	lunian		ide	PRODUCTION SPECIALIST		
Tide	Deputy Oil & C	Eas Inspector					

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

enced at thour, date! ##

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Notes: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Text'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Axtec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).