

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY
3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1090' FNL x 790' FWL, Section 31,
AT SURFACE: T26N, R5W
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO: | | SUBSEQUENT REPORT OF: |
|---------------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) Spud & Set Casing | | |

5. LEASE
Jicarilla Contract 155
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Jicarilla Gas Com "B"
9. WELL NO.
1E
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NW/4 NW/4 Section 31, T26N, R5W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
NM
14. API NO.
30-039-22087
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6596' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" hole on 8/6/79. Drilled to 310'. Set 8-5/8" casing at 300' and cemented with 315 sx 2% CaCl₂ cement. Circulated out 10 sx good cement.

Drilled 7-7/8" hole to TD and ran 4-1/2", 11.6# casing at 7576'. Cemented with 515 sx Class "B", 50:50 Poz with 6% gel, 2# medium tuf plug per sx, 0.2% friction reducer and 0.8% fluid loss additive. Tailed in with 100 sx Class "B" Neat cement.

Cemented second stage with 990 sx Class "B" Halliburton Lite 65:35 Poz with 6% gel, 2# medium tuf plug per sx, 0.2% friction reducer and 0.8% fluid loss additive. Tailed in with 100 sx Class "B" Neat cement.

Rig released on 8/22/79.
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.


18. I hereby certify that the foregoing is true and correct

SIGNED E. E. SVOBODA TITLE Dist. Adm. Supvr DATE 8/30/79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



RECEIVED

AUG 31 1979

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.