STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

DDV	ATD D	C	_ 1	Durna Fodo		Tell 0. <u>2</u>	
12101	ALB Energy		Lease	Burns Fede			
tion Zell: Unit B	Sec5T	wp. 26 N	Rge	7 W	County _R	<u>io Arriba</u>	
Vell: Unit B Sec. 5 Twp. 26 N			TYPE OF PR (Oil or God	00. M	ETHOD OF PROD. Flow or Art. Lift)	PROD. MEDIUM (Tbg. er Ceg.)	
per Hetion Oter	o Chacra		Gas	F	low	TBG	
Blan	co Mesa Ve	erde	Gas	F	low	TBG	
		PRE-FLO	OW SHUT-IN PE			ad? (Yes or No)	
Hour, date st	nut-in	Length of time shu		Si press. psig			
pletton 7/8/91 3 days Length of time shut-in			509 Si press. psig		Stabilized? (Yes or No)		
	7/8/91 + 3 days		•••••	451	r	10	
			FLOW TEST		oerer Lower Lowe	r	
nenced at (hour, dat	at (hour, date) * 7/11/91			Zone producing (Up			
TIME (hour, date)	LAPSED TIME SINCE*	Upper Completion	Lower Completion	PROD. ZONE TEMP.		REMARKS	
7/12/91	l day	521	423				
7/13/91	2 days	524	426		DEC	EINEU	
						2 1991	
					OIL CO	ON. DIV	
·							
duction rate o	201	D based on	Bbls. ii	n Hour	s Grav.	GOR	
s:351				(Orifice or Mete			
		MID-1	TEST SHUT-IN P	RESSURE DATA	\	Was as No.	
Hour, date shut-in Length of time s		hut-in	SI press. psig	Stabil	ized? (Yes or No)		
Upper Impletion Hour, date shul-in Lower Lower		Length of time s	bud in	SI press, paig		ized? (Yes or No)	

FLOW TEST NO. 2

Commenced at (hour, date) **				Zone producing (Upper or Lower):		
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		_ PROD. ZONE		
		Upper Completion	Lower Completion	TEMP.	REMARKS	
			1	!		
		1		····		
		1	:			
		 				
			•	!		
				6 mag mag mag no 1		
		-		•		
2.22			Ī	1 .		
			 			
		İ				
	<u> </u>	•	<u> </u>	·		
					Grav GOR _	
emarks:						
-marks		 ,				
		· · · · · · · · · · · · · · · · · · ·				
hereby certify th	hat the informati	ion herein contair	ned is true and co	mplete to the best of	my knowledge.	
pproved	SFP 121	991	19 C	DEKAL	B Energy Co.	
	il Conservation I		_ 19	Detator DEKAL	B Biller gy CO.	
INCW MICALO O	ii Conscivation i		, B	wMike Rai	nwater	
· /	11/1/	111111	_	,		
y	putti.	Stretza	<u> </u>	ide <u>agent</u>		
DEPUTY OIL & GAS INSPECTOR, DIST. #3			_	Angust	20 1001	
itle DEPUTT				Date August	40,1991	
-;-						

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).