API#

30-039-22421

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator <u>E</u>	BURLINGTON RESOURCE	CES OIL & GAS CO.		Lease	JICARILLA 153	3		Well No.	25
Location									
of Well:	Unit A Sect	36 Twp.	026N	Rge.	005W	County	RIO ARRIBA		
	NAME O	F RESERVOIR OR POO	L	Т	YPE OF PROD.	MET	HOD OF PROD.	PR	OD. MEDIUM
Upper					(Oil or Gas)	(Flo	w or Art. Lift)	(	Tbg. or Csg.)
Completion	MESAVERDE				Gas Flow		Flow		Tubing
Lower Completion	GALLUP/DAKOTA		Gas Flow		Flow		Tubing		
			FLOW SHUT-II	N PRESS	URE DATA			<del>'</del>	
Upper Completion	Hour, date shut-in Length of time shut-in			SI p	SI press. psig Stab		Stabilized? (Ye	s or No)	
	10/2/97	168 Ho	urs		380				
Lower Completion	10/2/97	120 Ho	urs		490				
			FLOW TE	EST NO.	1				
	at (hour,date)*	10/7/97			Zone producing (	Upper or l	Lower) LO	WER	
TIME	LAPSED TIME		SSURE		PROD. ZONE				
(hour,date)	SINCE*	Upper Completion	Lower Comp	letion	TEMP	REMARKS			
10/8/97	144 Hours	400	420			turn on lower zone.			
10/9/97	168 Hours	450	330						
								2 1838	
						0		ان آق	
roduction rate	during test						DIST	. <b>3</b>	
Oil:	BOPD based on	Bbls. in		Hours.	lours. Gra		<del></del>	GOR	
Gas:		MCFPD; Tested thru (C	Orifice or Meter)	:					
		MID-7	TEST SHUT-IN	PRESSU	RE DATA				
Upper Completion	Hour, date shut-in	Length of time shut-in		SI pro	SI press. psig		Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	Length of time shut-in		SI pre	SI press. psig		Stabilized? (Yes or No)		

FLOW TEST NO. 2

Commenced a	it (hour,date)**			Zone producing (Upper or Lower):				
TIME LAPSED TIME		PRESSURE		PROD. ZONE				
(hour.date)	SINCE**	Upper Completion	Lower Completion	ТЕМР.	REMARKS			
		ļ						
	<u> </u>							
					1			
·				<u> </u>				
			ļ					
			<u></u>					
Production	rate during test				; •			
				••	Grav. GOR			
Oil:	BOPD bas	ed on	Bbls, in	Hours.	Grav. GOR			
Gas:	_ <del>`</del>	MCFPD; Te	ested thru (Orifice or	Meter):				
Remarks:								
		<del></del>	li	es es the best of my l	nowledge			
I hereby ce	rtify that the informa	ition herein containe	d is true and complet	te to the best of my k	mowiedge.			
_		100	1. 10	Operator ///	luctor Resources Inc			
Approved		AN 05 1993	19	_ Operator y w	unique recursion			
	-			By Del	as dia			
New Me	xico Oil Conservatio	n Division		by <u>rest</u>	The state of the s			
Ву	Jahr	ing Role ty Oil & Gas 1	near	Title Golf	atin associati			
-	Deni	by Oil 2 Gas !	aspactor	•	in the second se			
Title	Бери	ty On te day i		Date				
					***			

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be connected on all multiple completions within seven days following recompletion and/or chemical or frac-ture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify
  the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so
  notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization, both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days if the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during flow Test No. 1.
   Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1

- except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gaz aone.
- 8. The results of the above described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division of Northwest New Mexico Packer Leakage Test form Revised 10/01/78 with all deadweight pressures indiqued thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).