STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is net to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	Marathon O	il Company	Lease	Jicarilla A	Apache N	7ell 16E	
Location of Well: Unit	A Sec. 34	7-p. 26N	Rge	5W	County _		
NAME OF RESERVOIR OR POOL			TYPE OF P	ROD.	AETHOD OF PROD. (Flow or Art. LHD)	PROD. MEDIUM (Tbg. or Cag.)	
Upper Blanco Mesa Verde			gas		flow	casing	
Completion Basin Dakota			gas		flow tubing		
		PRE-FL	OW SHUT-IN P	RESSURE DATA			
Upper Hour, date shut-in Length of time shut-in				Si press. psig S 417		Stabilized? (Yes or No)	
	14-93		5 days			yes	
Lower Hour, date shut-in Le		1 "	Length of time shutin 3 days		Stabilize	d? (Yes or No) Yes	
			FLOW TEST	NO. 1			
Consmenced at (hour, da	ite) *			Zone producing (Upper or Lowert			
TIME	LAPSED TIME	PRESSURE		PROD. ZONE			
(hour, date)	SINCE*	Upper Completion	Lower Completion	TEMP.	·	EMARKS	
11-14-93					Both zones	s SI	
11-15-93		346	770		Drabayen		
11-16-93		373	854		UN DEUZ 3 1993		
11-17-93		391	862		OIL CON. DIVI		
11-18-93		402	323		Flowin g Lowe r zone		
11-19-93		417	308		Flowing lwer zone		
Production rate d	uring test Sta	tic 8.1	Diff: 3.2	Orifice	: .875 Sta	atic Spring 500	
Oil:	BOPI	D based on	Bbls. in	Hours	Grav	GOR	
Gas:		мсғ	PD; Tested thru	(Orifice or Meter	r):	 	
		MID-TI	EST SHUT-IN P	RESSURE DATA			
Upper Completion Length of ti		Length of time shi	ul-in	SI press. psig	Stabilize	d? (Yes or No)	
Lower Hour, date shut-in		Length of time shi	Length of time shyt-in		Stabilize	d7 (Yes or No)	

FLOW TEST NO. 2

Zone producing (Upper or Lowerk

TIME (hour, date)	LAPSED TIME SINCE ##	PHESSURE		PROD. ZONE	•
		Upper Completion	Lower Completion	TEMP,	REMARK\$
			• •• · · · · · · · · · · · · · · · · ·		Processor (processor)
		• .			
roduction rate di	uring test				
Oil:	BOPI	D based on	Bbls. in	Ho	uis Grav GOR
325:		MCFF	D: Tested thru (Orifice or Me	eter):
					<u>-</u>
hereby certify tha	at the information	n herein containe	ed is true and con	aplete to the	best of my knowledge.
pproved	DEC 2 3 1	995			Marathon Oil Company
New Mexico Oil	Conservation D	ivisi on	·		omas M. Price Turpine
Progun	al Signed by CHAI	1245 6/3017 6 N			v. Engineering Tech.
	OIL & GAS INSPE	CTOR, DIST. #3	D:	12-	-20-93

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage ten shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tens shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture ucaument, and whenever temedial work has been done on a well during which the packer or the rubing have been dimurbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) ##

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has nabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the aumosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Providure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shur-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at furteen-minute intervals during the first hour thereof, and at houtly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone texts: all pressures, throughout the entire text, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least revice, once at the beginning and once at the end of each text, with a decadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).